Soft Surface Sanitizer HIL0091906



For use on soft surfaces such as: soft household surfaces, upholstery, fabric, upholstered couches, sofas, chairs, seat cushions, upholstered cushions, pillows, upholstered furniture, fabric window treatments, curtains, draperies, shower curtains, laundry, diaper bags, back packs, fabric hampers, pet bedding, blankets, upholstered car seats, stuffed animals, and toys. Active ingredients: Octyl decyl dimethyl ammonium chloride 3.255%, Dioctyl dimethyl ammonium chloride 1.302%, Didecyl dimethyl ammonium chloride 1.953%, Alkyl (C14, 50%; C12, 40%; C16, 10%) dimethyl benzyl ammonium chloride 4.340%, Other Ingredients: 89.150%.

Features & Benefits

Effectively controls malodors.

Effective soft surface sanitizer.

For all soft surfaces.

Item Number & Unit of Measure

Item Number	HIL0091906
Unit of Measure	1 gal Bottle

Specifications

Color	Yellow
Appearance	Clear
Fragrance	Lemon
Formula Type	Liquid

Dilution Ratio	1:64 - 1:1128
РН	12.00 - 13.00
Non-Volatile Matter	19.50 - 21.50%
EPA Registration #	6836-77-1658

Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

This product is not for use on medical device surfaces. Prepare a fresh solution daily or more often if the use solution becomes visibly diluted or soiled. TO SANITIZE **SOFT SURFACES:** For spot treatment only. Add 1 - 2 oz. per gallon of water. Apply use-solution with a sprayer. Hold bottle 6" - 8" from surface and spray until fabric is wet. Fabric must remain visibly wet for 5 minutes. Allow fabric to air dry (reapply as necessary). Visibly soiled areas must be cleaned prior to sanitizing. To Clean and Deodorize: Mix 1 oz. of Soft Surface Sanitizer per gallon of water to clean and deodorize hard, non-porous, non-food surfaces. Apply using a cloth, mop, sponge or sprayer. Wipe or allow to air dry. Cleaning **Solution:** Dilute 1 - 2 oz. per gallon of water for cleaning of kitchen counters, tables, walls, bathrooms, toilet seats, mopping floors and large routine applications. Apply to surfaces using cloth, mop or sponge. Remove excess liquid or allow surfaces to air dry. Deodorizing directions:Laundry: 1 oz. per load added during

the final rinse cycle deodorizes all offensive odors.**Carpets:** 1 - 2 oz. per gallon of water eliminates odors associated with urine, vomit, smoke, and mildew.

Reapply after cleaning for freshening effects. Allow to dry.**Pet Odors:** Use 4 - 6 oz. per gallon of water or desired concentration, for urine, feces, and vomit, in carpet and upholstery. Clean prior to application then spray onto affected areas. Test hidden area for colorfastness. Allow 10 minutes contact time. Then blot with clean cloth. Allow to





dry. Also effective on pet bedding and litter boxes.**Sewage Backup, Water Damage:** 2 - 4 oz. per gallon of water or desired concentration. Spray over affected areas before and after cleaning and extraction. Allow ten minutes contact time. Use proper ventilation; open windows.**WATER DAMAGE RESTORATION AGAINST ODOR-CAUSING BACTERIA AND FUNGI FOR HOME, INSTITUTIONAL AND INDUSTRIAL USE**:

This product is particularly suitable for use in water damage restoration situations against odor causing bacteria on the following porous and semi-porous materials: carpets, carpet cushions, subfloors, drywall, trim and frame lumber, tackless strip and paneling. Using appropriate dilution, saturate the affected materials with enough product to remain visibly wet for at least 10 minutes. Sewer Backup and River Flooding: During mitigation procedures, dilute 1 - 2 oz. of the concentrate per gallon of water, allowing for the diluting effect of absorbed water within saturated materials. Remove visible filth or heavy soil along with non-salvageable materials. Saturate all affected areas with a coarse spray device before and after cleaning and extraction.Carpets, Carpet Cushions and Other Porous Materials such as Subfloors, Drywall, Trim and Frame Lumber, Tackless Strip and Paneling: For water damage from a clean source, extract excess water. Test hidden area for colorfastness. Dilute 1 - 2 oz. of the concentrate per gallon of water, allowing for the diluting effect of absorbed water within saturated materials. Remove visible filth or heavy soil. Saturate all affected areas with a coarse spray device. Roll, brush or agitate into the materials and allow materials to remain visibly wet for 10 minutes. Follow with a thorough extraction. Dry rapidly and thoroughly. Special Instructions For **Cleaning Carpet Against Odor Causing Bacteria:** Use this product in industrial and institutional areas such as motels, hotels, and schools. Use on wetcleanable synthetic fibers. Do not use on wool. Vacuum carpet thoroughly prior to cleaning. Test fabric for colorfastness. For portable

extraction units: Mix 1 oz. of concentrate per gallon of water. For truck mounted extraction machines: Mix 1 - 2 oz. of concentrate per gallon of water and meter at 4 gallons per hour. For rotary floor machines: Mix 1 oz. of concentrate per gallon of water and apply at the rate of 300 - 500 sq. ft. per gallon. Do not mix this product with other cleaning products. Follow the cleaning procedures specified by the manufacturer of the cleaning equipment. After using the product, set the carpet pile and protect the carpet from furniture legs and bases while drying. Do not overwet. If applied to stain resistant nylon carpet, apply a fabric protector according to the manufacturer's directions.