

I W 6 1 0 S W

10" IN-WALL SUBWOOFER

Jamo[®]



SPECIFICATIONS

FREQUENCY RESPONSE*	24Hz - 100Hz
MAXIMUM OUTPUT*	109dB @ 70Hz
POWER HANDLING	200W RMS / 500W Peak
NOMINAL IMPEDANCE	8 Ohm
LOW FREQUENCY DRIVER	254mm (10") Fiberglass
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Sealed MDF Cabinet
INPUTS	Single Binding Posts
FINISH	Matte Black Polymer Veneer
DIMENSIONS	559mm H, 448mm W, 102mm D 22.0" H, 17.63" W, 4.0" D
CUTOUT DIMENSIONS	515mm H, 369mm W, 87mm D 20.25" H, 14.5" W, 3.4" D
WEIGHT	9.2kg (20.3 lbs)

*WITH JDA-500 AMPLIFIER DSP PRESET

DISCRETE LOW FREQUENCIES

A true subwoofer for both music and movies, the IW 610 SW provides clean, dynamic, balanced low frequencies while its in-wall design keeps it hidden from view.

HIGH PERFORMANCE ACOUSTICS

10" long-throw fiberglass woofer with reverse rolled surround provides dynamic, balanced, distortion-free low frequencies - all fitting within a traditional wall space.

MDF ENCLOSURE

The durable, robust MDF enclosure, provides accurate, powerful low frequencies while helping to isolate sound from neighboring rooms.

FLAT, MAGNETIC GRILLE

Magnetic, bezel-free, paintable grille blends seamlessly into even the most luxurious of living spaces and home theaters.