



Technical Data Sheet

3M™ Air & Vapor Through Wall Flashing Tape 3015TWF



[Product Details](#)



[Regulatory Info/SDS](#)

Product Description

3M™ Self-Adhered Through Wall Flashing Membrane 3015 TWF is specially designed for use as a through wall flashing and damp proof course. 3M™ 3015 TWF is an impermeable membrane with an aggressive, high tack acrylic pressure sensitive adhesive that does not require the use of a primer on most construction surfaces.

Product Features

- Exceptional puncture and abrasion resistance.
- Excellent adhesion to concrete, concrete block, anodized aluminum, galvanized metal, exterior gypsum sheathing and plywood. Primer not required in most applications.
- Flexible at low temperatures.
- Unique adhesive even adheres to damp surfaces that have not absorbed water, like metals, glass and plastics.
- Compatible with many building sealants including polyurethane, silicone and silane terminated hybrid sealants.
- Service temperature from -40°F to intermittently 240°F (-40° to 116°C).
- Can be applied from 0° to 150°F (-18° to 66°C)
- Resists UV exposure for up to 12 months.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Attribute Name	Test Method	Value
Color		Black
Adhesive Type		Acrylic
Backing		Polyethylene
Total Tape Thickness	ASTM D3652	0.4 mm (15.5 mil)
Film Thickness		0.19 mm (7.5 mil)
Liner		Polycoated Kraft

Attribute Name	Test Method	Value
Moisture Absorption	ASTM D570	CGSB 37GP56M
Water Vapor Transmission	ASTM E96 MASTM EthoASTM D B	0.03
Nail Sealability	ASTM D1970	127 mm (5 in) ¹
Puncture Resistance Membrane	ASTM E154	>170 N (>38 lb)

¹ Water Head After 3 Days Dry

Typical Performance Characteristics

Attribute Name	Value
Minimum Long Term Temperature Resistance	-18 °C (0 °F) ¹
Long Term Temperature Resistance	66 °C (150 °F) ¹
Low Temperature Flexibility	30 °C ²

¹ Long Term (day, weeks)

² Bend Test

Attribute Name	Test Method	Value
Elongation at Break	ASTM D412	>600 %
Tensile Strength	ASTM D412	>7 MPa (>1000 lb/in ²)
Lap Adhesion	ASTM D1876	>4.2 N/cm

Handling/Application Information

Surface Preparation

- To obtain the best adhesion, 3M™ 3015 TWF should be installed when outdoor temperatures measure above 0°F to 150°F (-18°C to 66°C). Excellent adhesion to concrete, concrete block, anodized aluminum, galvanized metal, exterior gypsum sheathing and plywood. Primer not required in most applications.
- Surfaces should be clean, free from dirt and debris and have not absorbed water.
- Surfaces should be free of any damaged, unsupported areas, sharp protrusions or voids.
- Concrete must be cured a minimum of 7 days before application.
- Block or brick walls should have mortar joints stuck flush.
- 3M™ 3015 TWF adheres to most common building materials. For difficult-to-stick-to surfaces, test adhesion before application. If needed, apply 3M™ Hi-Strength 90, 3M™ Hi-Strength 94 ET Spray Adhesive, 3M™ ScotchWeld™ Holdfast 70, or 3M™ Fastbond™ Contact Adhesive 30NF to prime the substrate prior to applying the membrane.

Application Techniques

- Overlap all joints by 50mm (2"). Keep 3M™ 3015 TWF back 12mm (½") to 25mm (1") from outside face of wall or veneer.
- Detail work must be carefully executed to ensure a continuously sealed building envelope: at all laps, seams, penetrations, and along top edges of 3015 TWF, apply a continuous bead of sealant such as 3M™ Polyurethane Sealant 540. Form end dams as required and use sealants at laps. Top or leading edge of 3M™ 3015 TWF must be sealed to prevent rain water from migrating behind the membrane.

Storage and Shelf Life

Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original packaging, out of direct sunlight. For best performance, use this product within 24 months from date of manufacture.

Available Sizes - Detailed

300mm (12 in), 400mm (16 in), 450mm (18 in) x 75 feet.

Roll size Theoretical Coverage

12" by 75 ft 75 ft²
(30.48 cm x 22.86 m) (7 m²)

16" by 75 ft 100 ft²
(40.64 cm x 22.86 m) (9.3 m²)

18" by 75 ft 112.5 ft²
(45.72 cm x 22.86 m) (10.45 m²)

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or

packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

ISO Statement

This product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Industrial Adhesives and Tapes Division
3M Center, St. Paul, MN 55144-1000
3M.com/iatd

3M is a trademark of 3M Company. ©3M 2025 (4/25)