



PDU41004 SWITCHED PDU SERIES



Designed for datacenters and other electrically demanding applications.

The CyberPower PDU41004, a 1U rackmount switched power distribution unit (PDU), provides 100-240V 15A output via 8 IEC-320 C13 receptacles from a single IEC-320 C14 input power plug. The switched outlet receptacles can be managed over the network by using the CyberPower Management Console, a web browser, and the RJ45 Ethernet port for network connection, or locally from the Power Control display. The PDU41004 offers outlets that can be turned on, turned off, or recycled on demand. Outlets can be programmed to address a number of needs including remote rebooting of locked equipment, load shedding, power sequencing, and locking out unauthorized loads.

With a three-year limited warranty, you can trust CyberPower's commitment to high quality.

TYPICAL APPLICATIONS

- Servers
- Network Devices
- Telecom Equipment

FEATURES

- Switched PDU: SNMP Network Interface and Switchable Outlets
- Automated notifications: Email, SMS Text, and SNMP Trap
- Phase: Single
- Amps: 15A (Derated to 12A)
- Volts: 100 - 240 V
- Frequency: 50Hz/60Hz
- Plug type: IEC-320 C14
- Outlets: 8 IEC-320 C13
- Outlet location: 8 Front
- Size: 1U Rackmount
- Warranty: Three-Year

SPECIFICATIONS

INPUT	
Cord Length	10 ft (3.0 m)
Derated Input Current	12 A
Input Frequency Range	50 Hz - 60 Hz
Input Plug Type	IEC-320 C14
Maximum Input Current	15A
Nominal Input Voltage	100 - 240 VAC
Phase	Single Phase
Plug Style	Straight

OUTPUT	
Controllable Outlets	8
Meter Readout	Power Control Display
Nominal Output Voltage	100 - 240 VAC
Outlet Type	8 x IEC-320 C13
Outlet - Number of Banks	1
Outlets - Front	8
Outlets - Total	8

PDU41004

SWITCHED PDU SERIES

SPECIFICATIONS

MANAGEMENT & COMMUNICATIONS	
Environmental Sensor	Optional, via RJ45
Hardware Connection Port	RJ45 Universal (RJ45)
LCD	Multifunction LCD
LED Indicators	Tx/Rx LINK Normal/Warning/Critical Status
Modular Expandability (Cascading)	Yes, via RJ45
Outlet Switching	Yes
SNMP / HTTP Remote Monitoring	IPv4, TCP/IP, UDP, SNMPv1, HTTP, NTP, DNS, Telnet, DHCP, SMTP, FTP, IPv6, SNMPv3, HTTPs, SSH, SSL, TLS, LDAP(S), RADIUS, Syslog, CLI, Windows AD
Upgradeable Firmware	Yes
PHYSICAL	
Adjustable Mounting Brackets	2 sets (1-Short, 1-Long)
Color	Black
Cord Retention Tray/ Cord Organizers	Yes
External Site Ground Pin	Yes
Form Factors Supported	Horizontal or Vertical Rackmount Wallmount
Material of Construction	Metal
Rack Height	1U

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	11.2 x 4.45 x 43.31 cm
Physical Dimensions - Width/Height/Depth (mm)	112 x 44 x 433 mm
Physical Dimensions - Width/Height/Depth (in.)	4.41 x 1.75 x 17.05 in.
Weight (kg)	2.1 kg
Weight (lbs.)	4.63 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	25.4 x 6.96 x 49.23 cm
Shipping Dimensions - Width/Height/Depth (mm)	254.0 x 69.6 x 492.25 mm
Shipping Dimensions - Width/Height/Depth (in.)	10.0 x 2.74 x 19.38 in.
Shipping Weight (kg)	3.63 kg
Shipping Weight (lbs.)	8.0 lbs.
ENVIRONMENTAL	
Operating Elevation	0 - 11,483 ft (0 - 3,500 m)
Operating Relative Humidity	0 to 95% (non-condensing)
Operating Temperature	32 to 140 °F (0 to 60 °C)
Storage Elevation	0 - 49,213 ft (0 - 14,999 m)
Storage Temperature	5 to 149 °F (-15 to 65 °C)
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL62368
WARRANTY	
Extended Warranty Option	WEXT5YR-PDU1A
Product Warranty	3-Year Limited