


INCANDESCENT/LED 12V HYBRID ACCENT



15384 AZT, AZT 20L, AZT 24, BBR, BKT, BKT 24, CO - MINI ACCENT

| | | |
|--------------------------------------|--|--|
| Description | For uplighting only (spotlighting, cross-lighting, grazing). | |
| Ordering Guide & Finish | 15384 AZT - Textured Architectural Bronze, Aluminum 15384 AZT 20L - Same as 15384 AZT. 20-W MR-16, FL 36° included. 15384 AZT 24 - Same as 15384 AZT. Bulk packed in 24 (unbreakable master) 15384 BBR - Bronzed Brass, Brass 15384 BBR 20L- Same as 15384 BBR. 20-W MR-16, FL 36° included. 15384 BKT - Textured Black, Aluminum 15384 BKT 24 - Same as 15384 BKT. Bulk packed in 24 (unbreakable master) 15384 CO - Unfinished Copper. Extruded copper cowl. Die-cast brass knuckle/stem. | |
| Housing | Cast Aluminum, Cast Brass or Unfinished Copper. Heat resistant flat glass lens is fully sealed. | |
| Lamp Base | 12V Incandescent bi-pin, high temperature porcelain socket  | |
| Supplied Lamp | Lamp not supplied unless noted. Halogen light source. | |
| Incandescent Lamp Options | Power usage at 12V AC input VA MAX: 50-W(VA) MR-16 35-W(VA) Max. on 15384CO 20-W(VA) Max. Canada see page 161 | |
| LED Lamp Options | 4W (18000-18011) see page 159 Compares to 20W Halogen 6W (18012-18020) see page 159 Compares to 35W Halogen | |
| Wiring | 35" of usable #18-2, SPT-1-W leads. Cable connector supplied | |
| Mounting Acces. Included | 8" In-ground stake | |
| Optional Mounting Accessories | 15601 - Surface Mounting Flange 15607 - Surface Mounting Flange 15609 - Junction Box Mounting Bracket | 15647 - 90° Elbow 15649 - Stem Coupler 15645, 15656, 15657, 15658 or 15570 - Stems |
| Optional Lens Accessories | 15675 LIN - Linear Lens 15676 FRO - Frosted Lens 15679 BK - Hexcell Louver Shield 15686 BL - Blue Filter | |
| Notes | See page 200 for photometrics. Copper will naturally patina over time. | |

 Denotes fixture is compatible with incandescent or LED lamps.