

2024 Specification Sheet - English

**LONG DESCRIPTION –**

Long Description Marketing Copy

Twin-hammer impact mechanism provides high performance and reliability. Button to switch between forward and reverse rotation. One-piece handle and impact housing casting provide long life. Super Spool permits quick switches between open center and closed-center hydraulic systems

PRODUCT NAME –

Page Title

Impact Wrench - 1/2" 7/16 Hex

PRODUCT OVERVIEW –

Marketing Text 1

Twin-hammer impact mechanism provides high performance and reliability

Marketing Text 2

Button to switch between forward and reverse rotation

Marketing Text 3

One-piece handle and impact housing casting provide long life

Marketing Text 4

Super Spool permits quick switches between open center and closed-center hydraulic systems

Marketing Text 5

Heat-insulated handle, ergonomically positioned for comfort

Marketing Text 6

Well balanced for comfortable operation

Marketing Text 7

Most durable and longest life of any 1/2" wrench on the market

Marketing Text 8

Includes the 49314 heavy duty 1/2" square drive adapter, toughest adapter on the market

PRODUCT SPECIFICATION –

Product Specification 1

Accessory : 54923 HTMA Male Coupler, 54925 HTMA Female Coupler, 49314 Heavy Duty 7/16" Hex by 1/2" Square Drive Shank Adapter

Product Specification 2

Accessory : NR1 Nut Runner With Adapter For 5/8", 1/2", 13/16" and 1.000" Square Nuts

Product Specification 3

Accessory : NR2 Nut Runner With Adapter For 1.000", 1-1/8"

Product Specification 4

Capacity : 7/16 IN

Product Specification 5

Flow Range : 4 - 10 GPM (15 - 38 LPM)

Product Specification 6

Handle Type : Heat-Insulated

Product Specification 7

Height : 10.600 IN (269.000 MM)

Product Specification 8

Hydraulic System : Super Spool Selector For Either Open-Center Or Closed-Center

Product Specification 9

Includes : 49314 Heavy Duty 1/2 IN Square Drive Adapter

Product Specification 10

Length : 8.200 IN (208.000 MM)

Product Specification 11

Operating Pressure : 1000 - 2000 PSI (69 - 140 BAR)

Product Specification 12

Optimum Flow Range : 5 - 8 GPM (19 - 30 LPM)

Product Specification 13

Pressure Port : 3/4 - 16 SAE O-Ring

Product Specification 14

Return Port : 3/4 - 16 SAE O-Ring

Product Specification 15

Torque Rating : 400 FT-LB At 8 GPM (542 N-M AT 30 LPM) Maximum, 400 FT-LB 8GPM (542 N-M At 30 LPM) Minimum

Product Specification 16

Weight : 7.400 LB (3.400 KG)

Product Specification 17

Width : 4.200 IN (107.000 MM)