84101 84102 84103 INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION

- 1. Attach mounting bracket (4) to outlet box(1) with box screws (5).
- 2. Thread two mounting screws (11) through the mounting bracket (4).
- 3. Pull out the outlet wire and ground wire from the outlet box, make wire connections with wire nut (3) as follow:
- --Connect the smooth-coated wire (marked) or Black wire from fixture to the Black wire (9) from power source.
- -- Connect the ribbed-coated wire (marked) or White wire from fixture to the White wire (2) from power source.
- --Attach the house ground wire to mounting bracket (4) with the ground screw (12). Connect it to the fixture ground wire (10) with the wire nut (3).

4. Attach the fixture backplate (6) to the outlet box (1) through the mounting screws(11), secure it with the rubber (7) and ball nuts (8).

5. To prevent moisture from entering the outlet box and the fixtures mounting plate causing a short, apply a bead of clear caulk to outline the outside of the fixtures mounting plate where it meets the wall. Leave a small space at the bottom to allow any condensation or moisture to escape.

6. Turn on the power.

INSTALLATION IS NOW COMPLETED

