

SAFETY DATA SHEET

1. Identification

Product identifier New Generation™ Wheel Bearing Grease for Disc and Drum Brakes - 14 oz

Other means of identification

Product Code No. SL3110 (Item# 1007852)

Recommended use Wheel bearing grease for disc and drum brakes

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsSerious eye damage/eye irritationCategory 2AEnvironmental hazardsHazardous to the aquatic environment, acuteCategory 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes serious eye irritation. Harmful to aquatic life. Harmful to aquatic life with long lasting

effects.

Precautionary statement

Prevention Wash thoroughly after handling. Wear eye/face protection. Avoid release to the environment.

Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	50 - 60
distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	40 - 50
phosphorodithioic acid, o.o-di-c1-14-alkyl esters, zinc salts		68649-42-3	3 - 5

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Inhalation If breathing stops, provide artificial respiration. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation. Call a physician if symptoms develop or persist.

Wash off with plenty of water. Remove and isolate contaminated clothing and shoes. Get medical Skin contact

attention if irritation develops and persists. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Rinse mouth. If material has been swallowed and the exposed person is conscious, give small

quantities of water to drink. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if

symptoms occur.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Irritating to mouth, throat, and stomach.

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Ingestion

Specific hazards arising from

Use fire-extinguishing media appropriate for surrounding materials.

None known.

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Cool containers exposed to heat with water spray and remove container, if no risk is involved.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up The product is immiscible with water and will spread on the water surface. Prevent product from entering drains.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Avoid dust formation. Clean surface thoroughly to remove residual contamination. Sweep up or vacuum up spillage and collect in suitable container for disposal.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Provide adequate ventilation. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid release to the environment. Use care in handling/storage. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities Keep containers tightly closed in a dry, cool and well-ventilated place. Do not store in direct sunlight. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Oc

	Туре	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
,		2000 mg/m3	
		500 ppm	
US. ACGIH Threshold Limit	t Values		
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide t	o Chemical Hazards		
Components	Туре	Value	Form
•		1800 mg/m3	
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1600 Hig/ilis	
distillates (petroleum), nydrotreated heavy naphthenic (CAS	Ceiling STEL	10 mg/m3	Mist.
distillates (petroleum), hydrotreated heavy naphthenic (CAS	·	•	Mist. Mist.
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) distillates (petroleum), solvent-dewaxed heavy	STEL	10 mg/m3	
distillates (petroleum), hydrotreated heavy naphthenic (CAS	STEL TWA	10 mg/m3 5 mg/m3	

Biological limit values

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Wear protective gloves such as: Latex. Rubber. Hand protection

Wear suitable protective clothing. Other

SDS US

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

> NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Solid. Physical state **Form** Grease. Amber. Color

Odor Mild petroleum. **Odor threshold** Not available. Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

range

680 °F (360 °C) estimated

> 450 °F (> 232.2 °C) Flash point

Evaporation rate Slow.

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower Not available.

(%)

Flammability limit - upper

Not available.

(%)

< 0.1 mm Hg @ 68 °F Vapor pressure

Vapor density > 5 (air = 1)

0.9 Relative density

Solubility(ies)

Insoluble. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature 500 °F (260 °C) estimated

Not available. **Decomposition temperature Viscosity** Not available. Percent volatile Not available.

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials. Incompatible materials Acids. Strong oxidizing agents. **Hazardous decomposition** Carbon oxides. Metal oxides.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation. **Eye contact** Causes serious eye irritation.

Ingestion Irritating to mouth, throat, and stomach.

Symptoms related to the physical, chemical and

toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

Information on toxicological effects

Acute toxicity

Product Species Test Results

New Generation™ Wheel Bearing Grease for Disc and Drum Brakes - 14 oz

Acute Dermal

LD50 Rabbit 3226 mg/kg

Oral

LD50 Rat 5263 mg/kg

Components Species Test Results

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

distillates (petroleum), solvent-dewaxed heavy paraffinic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-65-0)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not likely, due to the form of the product.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components Species Test Results

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 1000 mg/l, 48 hours

Material name: New Generation™ Wheel Bearing Grease for Disc and Drum Brakes - 14 oz

^{*} Estimates for product may be based on additional component data not shown.

 Components
 Species
 Test Results

 Fish
 LC50
 Rainbow trout, donaldson trout
 5000 mg/l, 96 hours

(Oncorhynchus mykiss)

(- , , , ,

phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts (CAS 68649-42-3)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 1 - 5 mg/l, 48 hours Fish LC50 Fathead minnow (Pimephales promelas) 1 - 5 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste

disposal site. Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts (CAS 68649-42-3)

CERCLA Hazardous Substance List (40 CFR 302.4)

phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts (CAS 68649-42-3)

CERCLA Hazardous Substances: Reportable quantity

Not listed

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

^{*} Estimates for product may be based on additional component data not shown.

Food and Drug Not regulated.
Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard

Serious eye damage or eye irritation

categories

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
phosphorodithioic acid, o,o-di-c1-14-alkyl esters,	68649-42-3	3 - 5	

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts (CAS 68649-42-3)

US. Massachusetts RTK - Substance List

Not listed.

US. Pennsylvania Worker and Community Right-to-Know Law

phosphorodithioic acid, o,o-di-c1-14-alkyl esters, zinc salts (CAS 68649-42-3)

US. Rhode Island RTK

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 2.2 %

51.100(s))

Consumer products Not regulated

(40 CFR 59, Subpt. C)

State

Consumer products Not regulated

VOC content (CA) 2.2 % VOC content (OTC) 2.2 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 12-17-2019
Prepared by Dustin Kern

Version # 01

DisclaimerThe information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: New Generation™ Wheel Bearing Grease for Disc and Drum Brakes - 14 oz

No. SL3110 (Item# 1007852) Version #: 01 Issue date: 12-17-2019 8 / 8