

Little Giant®



*A 5'6" person with a 12" vertical reach

Part #	Model	StepLadder Max Reach*	Extension Max Reach*	Rung Depth	Storage Width	Storage Depth	Weight
13948-001	8'	12' 2"	15' 10"	3"	2' 4"	7"	43.5 lbs
13947-001	7'	11' 2"	14'	3"	2' 4"	7"	40.3 lbs
13946-001	6'	10' 3"	12' 1"	3"	2' 1"	7"	35 lbs

1-YEAR LIMITED WARRANTY

TELECOMBO™

COMBINATION LADDER | TYPE IAA 375 LBS RATED | OSHA + ANSI COMPLIANT



**Little
Giant**
Ladder Systems



PRODUCT DESCRIPTION

The Quick-Latch™ hinge allows users to quickly verify that the hinge is engaged and safe to climb. Designed with a contouring grey non-marring wall pad that spans the width of the ladder for better weight dispersal and reducing wall damage. Equipped with wide flare feet on the functional rear section to give added stability when climbing from either side of the ladder. The ladder is equipped with Sure-Set™ feet that can be used in the pad or spiked foot position outside providing additional safety while climbing. The non-conductive fiberglass 3-IN-1 Telecombo gives you the versatility of an A-Frame, leaning, and extension ladder all-in-one ladder.

STABILITY AND SAFETY COMBINED

THE TELECOMBO WAS DESIGNED TO MAKE TECHNICIAN'S JOBS SAFER AND EASIER.

1. WALL PAD

Large full width, non-marring pad for added stability. Works on flat walls, corners, poles and studs.

2. QUICK-LATCH™ HINGE

For safe transition from extension to stepladder.

3. WIDE 3 INCH STEPS

All day comfort.

4. BUBBLE LEVEL

Always climb at the correct lean angle.

5. GROUND CUE®

Makes an audible click when you have reached the final step of your descent.

6. WIDE FLARE FEET

For more stability while climbing the rear section while climbing in the stepladder position.

7. SURE-SET FEET™

Adds extra stability on job sites and can be used in either the pad or spike foot position.



 NON-CONDUCTIVE FIBERGLASS

