



**MATERIAL**

PLASTIC HOUSING : ABS high-impact UL94V-0 thermoplastic

INSERT:Brass 3604 surface gold plating

**PHYSICAL CHARACTERISTICS**

OPERATING TEMPERATURE RANGE : -10°C TO 60°C

STORAGE TEMPERATURE RANGE : -40°C TO 68°C

HUMIDITY : 10%~90%RH

**ELECTRICAL**

IMPEDANCE: 75 ohm

FREQUENCY RANGE: 0~3 GHz

WORKING VOLTAGE: 250 VRMS max.

DIELECTRIC WITHSTANDING VOLTAGE: 500VRMS min.

VSWR: 1.35 max

CONTACT RESISTANCE: 1.Center Contact: 5 Milliohms Max.

2.Outer Contact: 1 Milliohms Max.

INSULATOR RESISTANCE: 1000 Megohms min.

Colors Available: Light Almond & White

Scale	1.5:1	All Copy Rights Reserved	
3rd Angle Projection		SPEAKER BINDING POST KEYSTONE INSERT, GOLD-PLATED	
Unit	mm	SCP P/N	
Date	2015-09-16	<b>241RD-XX</b>	
Tolerance			
~20	~50	~150	150~
±0.2	±0.4	±0.5	±1.5
			ANGLE
			±2°
Drawn by		Checked by	
FHL		Santiago	