

Project Name:	
Location:	
Item #:	Qty:
Model:	

15 INCH SHALLOW DEPTH OUTDOOR BUILT-IN UNDERCOUNTER ICE MAKER

MODEL:

MIM25CO



MIM25CO

ELECTRIC -

115V / 60Hz / 1Ph International voltage available 6' (2m) NEMA 5-15P cord set included



3RD PARTY APPROVALS -



MAXX ICE WARRANTY (USA / CANADA) -

Contact Maxx Ice for warranty statement at TechnicalServices@TheLegacyCompanies.com or 877.368.2797

The Legacy Companies • 3355 Enterprise Avenue, Suite 160 • Fort Lauderdale, FL 33331 Sales: 954.202.7419 • Sales@TheLegacyCompanies.com • www.maxx-ice.com

The Maxx Ice MIM25CO is designed to perform in exacting outdoor environments, producing up to 25 pounds of crescent ice cubes per day. Its front-breathing design allow for built-in applications under a countertop and flush with your cabinets, while the fact that it does not need a drain line makes installation in a wide variety of locations a breeze. A shallow depth of 18.8 inches provides even more flexibility; install even in tight spaces that cannot accommodate a traditional 24 inch deep unit. The full stainless steel exterior, protective louvered toe-kick, and sturdy adjustable feet also allow you to install as a freestanding unit. Quiet operation is an added benefit to this type of ice maker, which is the perfect combination of style, performance, and practicality anywhere outdoors.

FEATURES AND CONSTRUCTION —

- High quality stainless steel exterior stands up to the harsh outdoor environment
- Produces up to 25 lbs of ice per day, over 5x as much as a standard household freezer ice maker
- Ice storage bin holds up to 22 lbs and is removable for easy access to the ice
- The interior is a freezer so the ice stays frozen no drain required
- Shallow depth of 18.8 inches allows installation in narrow spaces while still fitting perfectly in standard 24 inch depth applications
- Stainless steel door with handle is stylish and field-reversible for left or right handed operation (right hinged standard)
- Door-close assist feature forms a strong seal when door is closed and also prevents accidental opening
- Simple and worry-free On/Off switch is located at the front of the unit for easy access when unit is built-in
- Automatic shutoff feature to stop the unit from operating when the ice bin is full
- Adjustable feet for leveling the unit and installing at the perfect height
- Environmentally friendly R600a refrigerant
- The unit must be periodically manually defrosted
- Includes ice scoop and water inlet hose

DAILY ICE PRODUCTION -

ICE BIN STORAGE CAPACITY

MIM25C0 22 lbs (10 kg)

OPERATING REQUIREMENTS -

Ambient Air Temperature Range..... 50° to 100°F (10° to 38°C) Water Temperature Range....... 40° to 90°F (4° to 32°C) Water Usage per 100 lbs of ice...... 12.6 Gallons (47.7L) Water Supply Line Connection....... 1/4" O.D. Compression Water Pressure Range:


Min PSI..............20 Max PSI80*
Min Bar...........1.0 Max Bar..........5.5

*Above 75 PSI requires a regulator


Energy Consumption per 100 lbs of ice:

MIM25C0 9.7 kWh/100 lbs


TOP VIEW




FRONT VIEW



SIDE VIEW



CRESCENT CUBE (ACTUAL SIZE)







MODEL	EXTERNAL Dimensions	DAILY ICE PRODUCTION (70°F Air / 50°F Water)	ICE BIN STORAGE Capacity	NET WEIGHT / Shipping Weight	AMP DRAW (Making / Harvesting)	REFRIGERANT And Charge Size	ELECTRICAL
MIM25CO	14.6" x 18.8" x 33.6" (371 x 476 x 855 mm)	25 lbs (11.3 kg)	22 lbs (10 kg)	64 lbs (29 kg) 77 lbs (35.2 kg)	1.9A / 1.5A	R-600a 3.88oz (110g)	115V / 60Hz / 1Ph

INSTALLATION -

- All ventilation from front, limited vent in the back of unit no additional clearance required around sides of unit
- Requires incoming water line no drain required