

TASKI[®] swingo 1650 B

Large battery-powered automatic scrubber drier

Key features

- Increased working autonomy
- Excellent cleaning result and immediately dry floors
- Simplicity and ergonomic
- Easy maintenance

Increased working autonomy

The large 85-litre tank and the highly efficient IntelliFlow-system reduce water consumption significantly. Clean up to 2,500 m² without time consuming tank filling stops. Reduced energy consumption and high capacity batteries allow a run time of more than four hours before re-charging.

Excellent results and immediately dry floors

The brushes perfectly follow the floor profile, delivering ideal soil removal. Thanks to the w-shaped squeegee, the TASKI swingo 1650 B scrubber drier delivers a best-in-class drying result. The machine can be used at any time of the day, while reducing the potential risk of slip-fall accidents caused by wet floors.

Simplicity and ergonomics

With excellent ergonomics and simple, intuitive controls, the machine reduces operator fatigue and minimizes training.

Easy maintenance

All components needing frequent cleaning/maintenance are color-coded in yellow and can be easily removed within seconds. The machine's self explanatory dashboard promotes simple training and indicates maintenance intervals, ensuring the best results and extending the lifetime of the TASKI swingo 1650 B machine.







TASKI[®] swingo 1650 B

| Description | | | |
|---|--------------|---|------------------------|
| Theoretical performance | 2925 m²/h | Dimensions (L x W x H) | 154 x 69 x 118 cm |
| Working width | 65 cm | Door pass through width (w/o squeegee) | 70 cm |
| Squeegee width | 95 cm | Brush system | 2 x 33 cm |
| Solution tank | 85 L | Brush pressure | 0.32 N/cm ² |
| Recovery tank | 85 L | Cleaning speed | 4.5 km/h |
| Rated voltage | 24 V | Maximum ramp | 2.0 % |
| Nominal consumption | 1,200 W | Sound level | 62 dB(A) |
| Battery capacity (maximum) | 180 Ah/C5 | Protection class (BMS/non BMS) | II/III |
| Battery run time | over 4 hours | Approvals | CE/CB test certificate |
| Machine weight ready for use (including water) | 330 kg | | |

| Model | Article code |
|-----------------------|--------------|
| TASKI swingo 1650 B | |
| TASKI swingo 1650 BMS | |

| Accessories/Additional parts | Article code |
|--|--------------|
| Pad drive harpoon grip 33 cm (2 required) | 7515515 |
| Scrubbing brush standard 33 cm (2 required) | 7515516 |
| Scrubbing brush washed concrete 33 cm (2 required) | 7515517 |
| Scrubbing brush abrasive 22 cm (2 required) | 7515518 |
| Filling hose with universal coupling | 8502830 |
| TASKI IntelliDose kit for swingo 1650 | 7516240 |

Description of features

BMS (Battery Management System): The battery charger is integrated in the machine. A monitoring system prevents deep discharging of the battery and controls the charging process.

IntelliFlow (Cleaning Solution Dosing): The IntelliFlow system allows for a speed-dependent supply of cleaning solution. This feature ensures that the amount of solution dosed onto the floor is always constant – no matter how fast the machine is operating. The result? No puddles in curves and turns as well as a significant saving in cleaning solution, leading to significantly increased productivity of the machine.

