



D204

IP VIDEO DOOR STATION

Full Stainless-Steel • Fence Assembling Edition





GENERAL		VIDEO
Housing	Front panel 3,0 mm (0,12 in) brushed Stainless-steel, galvanized steel laterals powder coated RAL 9007, door with cylinder lock and 2 keys	Camera
Doorbell button	Stainless-steel button with illuminated LED Ring	Night-vision
Nameplate	Illuminated	
Mounting type	Fence assembly	AUDIO
Power supply	15 V DC (power 110 - 240 V AC) or Power over Ethernet (PoE 802.3af Mode-A)	Audio comp
Weight	12 kg	Audio strear
Connectors	Power, electric door opener/strike, door chime, door opener button, network	
Weather protection	Yes, IP65	NETWO
Approvals	CE, IC, FCC, IP65	WiFi
Dimensions	550 x 379 x 113 mm (H x W x D) 21,65 x 14,92 x 4,45 in (H x W x D)	Ethernet
Operating conditions	-20 to +40°C / -4 to 104°F Humidity 10 to 85 % RH	МОТІОМ
	(non condensing)	Type
	Video Door Station, front panel, fence assembly housing, power supply unit	Detection a
Scope of delivery	(world-wide, 110 - 240 V), DIN-Rail power supply sold separately, screw package, quickstart guide, 2 x 1m antenna extension cable, 2 x external antenna	Range
EAN	4260423860155	INTEGR
Warranty	see www.doorbird.com/warranty	WiFi
		Sensor
CURRENT SYST	TEM REQUIREMENTS	22

VIDEO		
Camera	HDTV 720 p, dynamic (VGA - HDTV)	
Lens	High-end ultra wide-angle hemispheric lens 180° horizontal, 90° vertical, straightened, IR-capable	
Night-vision	Yes, light sensor, automatic IR-cut filter, 12 IR-LEDs	
AUDIO		
Audio components	Speaker and microphone, echo and noise cancellation	
Audio streaming	Two-way duplex	
NETWORK		
WiFi	802.11 b/g/n 2.4 GHz	
Ethernet	Connector, PoE	
MOTION SENSOR		

INTEGRATED WIRELESS MODULES		
WiFi	2,4 GHz, external antenna	
Sensor	433 MHz, external antenna	

CURRENT SY	CURRENT SYSTEM REQUIREMENTS	
Mobile device	Latest iOS on iPhone/iPad, latest Android on Smartphone/Tablet	
Internet	High-Speed landline broadband internet connection, DSL, cabel or fiber, min. 500 kbs uploadbandwith, no socksor proxyserver	
Network	802.11 b/g/n 2.4 GHz or Ethernet network, with DHCP	
Recommended installation height	Camera lens should be at a min. height of 125 cm (49 in)	

## OPTIONAL ACCESSORIES

Sold separately see www.doorbird.com/buy

Special remarks:

The assembly requires professional skills or technician.

## **TECHNICAL DRWAINGS**



Front panel, data in mm Material thickness: 3,0















