



**NOTES:**

**ELECTRICAL:**

1. VOLTAGE RATING:125 VAC RMS
2. CURRENT RATING:1.5AMP
3. CONTACT RESISTANCE:100MILLIOHMS MAX
4. INSULATION RESISTANCE:1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH:750 VAC RMS 60Hz, 1MIN

**ENVIRONMENTAL:**

1. STORAGE:-40° TO +85°
2. OPERATION:0° TO 70°

**MECHANICAL:**

1. HOUSING MATERIAL: ABS ;
2. PANEL FRAME:CARBON STEEL, POWDER, COATING IN BLACK COLOR, Spcc1.5mm;
3. PCB MATERIAL:FR-4 T=1.6mm;
4. IDC MATERIAL:PC ,CONTACT:PHOSPHOR BRONZE; WITH NICKEL PATING;
5. RJ45 JACK LIFE:750 TIMES MIN;
6. IDC LIFE:200 TIMES MIN;
7. WIRE:AWG 22-26;

SYM	Number	Bill No. of Alteration	Signature	Date	Material			Item No.			
					Angles Projection	Size	Scale	Unit	DWG No.		
Drawn	Ding jian bo	2016. 1. 12	Tolerance			A4	X:1	mm	Part Name		48Ports Cat5e UTP Patch Panel
Checked	Ge pei jun	2016. 1. 12	0. 00-20. 00 ±0. 10 20. 00-50. 00 ±0. 15 50. 00-100. 00 ±0. 20 100. 00- ±0. 25 Angle ±30°	ERP							
Approved	Wang wei jun	2016. 1. 12			Sheet	1 OF 1	Version: A/0		Part No.		