



Model #: CP585LCD

UPC: 649532015856

MSRP: \$99.99



The Intelligent LCD Series CP585LCD UPS is ideal power protection for individuals running a stand-alone PC in their home or office.

Real-time system vitals can be viewed from the Intelligent Crystal-Blue LCD display, and the unit can be conveniently mounted in a workstation cabinet or directly on the desktop. LCD diagnostics include Input Voltage Level, Output Voltage Level, Battery Capacity, Runtime, Load Level, On Battery, Overload, Wiring Fault, and Silent Mode.

It also includes PowerPanel PE™ Power Management software which monitors the vitals of the UPS and will safely shutdown your system in case of a power outage. Composite integrated circuitry offers advanced lightning protection and also guards against surges, spikes, sags, brownouts and other power abnormalities.

This rugged unit is equipped with an RJ11/45 port, which protects against surges from phone, modem, network, and broadband disruptions. The small footprint design is ideal for horizontal, or vertically placement, and is even designed for wall-mountability. An HID-compliant USB port allows for connectivity of both PC and Mac systems. The unit is also perfect for protecting other electronics such as monitors, printers, scanners, speakers, fax machines, CD/DVD players, and iPods.

Cyberpower guarantees this product for 3-years, and has a \$175,000 connected equipment guarantee.

- **Intelligent LCD Diagnostic Display:** The innovative front panel LCD can be used to display detailed information on the UPS status and current power conditions. The LCD displays 9 different diagnostics: Input voltage level, Output voltage level, Battery capacity, Runtime estimate, Load level, On battery, Overload, Fault Condition, and Silent mode.
- **EMI/RFI -** Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or “humming” that occurs over telephone lines or stereo electronics.
- **Transformer-spaced Outlets -** Widely spaced outlets allow you to conveniently add large transformer-based plugs without compromising the utility of other outlets.
- **USB Connectivity -** An HID-compliant USB port enables full integration with built-in power management and the auto shutdown features of Windows, Linux, and Mac OS X.
- **PowerPanel PE™ Smart Management Software –** In event of a power outage, PowerPanel PE saves your open files and will “Hibernate” your PC to increase the run-time on the UPS unit. PowerPanel is quickly and easily installed on any Windows-based PC and is designed to utilize minimal system resources. Diagnostic screens give immediate visuals of the UPS’s status, and also include the following features: Silent operation mode, configurable system notifications, automatic self tests, adjustable high/low voltage warnings, event/data logging, and scheduled shutdowns.
- **LED Indicators -** LED status lights indicate Power-On and wiring faults.
- **Audible Alarms -** Audible tones identify when the unit is running off battery power, unit overloads, and low battery.
- **Convenient Mounting –** Multiple mounting options: horizontal, vertical, cabinet, and wall.
- **Resettable Circuit Breaker -** Convenient unit reset switch in case of an overload.
- **3-year Warranty -** CyberPower will replace damaged units if within 3 years of purchase date. We stand behind our products and guarantee quality. CyberPower also offers a #1 rated technical support team that will assist you with product, installation, or warranty concerns --- Free of Charge!
- **ISO & Safety Certifications -** All CyberPower manufacturing facilities are ISO-9001 Quality Tested. Our products are also certified by the FCC, cUL, and UL.
- **Windows Vista™ compatible -** Our Power Management software has been fully tested and is compatible with Windows 200x, Server, XP, and Vista.



Technical Specifications

General	
Model #	CP585LCD
UPS Topology	Standby
Input	
Voltage	90 - 140V
Frequency	57 - 63Hz
Plug Type	NEMA 5-15P
Cord Length	6 ft
Output	
VA	585
Watts	335
Automatic Voltage Regulation	No
On Battery Waveform	Simulated Sine Wave
Outlets - Total	8
Outlets - Battery & Surge	4 x NEMA 5-15R
Outlets - Surge-Only	4 x NEMA 5-15R
Transfer Time	4 ms
Battery	
Runtime at Full-Load	2 Minutes
Runtime at Half-Load	9 Minutes
Battery Specification	1 x 12V/7Ah
Surge Protection and Filtering	
Surge Suppression	1030 Joules
Phone / Ethernet RJ11 / RJ45	1 x RJ11/45 Combo (One-in/One-out)
Coax Protection RG6	None
Management & Communications	
Indicators	Multifunction LCD Readout
USB Port	1 x HID Compliant
Serial Port	None
Software	PowerPanel Personal Edition
SNMP / HTTP Remote Monitoring	Not Available
Physical	
Dimensions (WxHxD)	11" x 6.5" x 3.5"
Weight	11.5 lbs.
Warranty	
Product Warranty	3-year warranty. Free Tech Support.
Connected Equipment Guarantee	Lifetime
CEG Amount	\$100,000