

CyberPower

P6WUC15 WALL-TAP SURGE PROTECTION

Protect home and office computers, and electronics.

The P6WUC15 Surge Protector Wall-tap with USB safeguards common home and office devices, such as computers and electronics, by absorbing spikes in energy caused by storms and electrical power surges. It provides 1800 joules of protection, has 6 surge-protected outlets, and a wall-tap plug. One USB-A port (2.4 Amps) and one USB-C port (15W) charge mobile devices including smartphones, digital cameras, and others. The P6WUC15 also features Protected and Grounded LED status indicators, and an impact-resistant casing.

The P6WUC15 also features metal oxide varistor (MOV) technology. This surge protector wall-tap comes with a One-Year Limited Lifetime Warranty and a Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 1800 J
- Outlet number: 6
- Outlet type: NEMA 5-15R
- USB-A charge port: 1 (2.4A)
- USB-C charge port: 1 (15W)
- LED indicators: Protected, Grounded
- Plug type: NEMA 5-15P
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$100,000

SPECIFICATIONS

| INPUT | |
|-----------------------|---------------|
| Input Plug Type | NEMA 5-15P |
| Input Voltage Range | 100 - 125 VAC |
| Maximum Input Current | 15 A |
| Plug Style | Wall-tap |

| OUTPUT | |
|--------------------------|-------------------------|
| Outlet Type | 6 x NEMA 5-15R |
| Outlets - Total | 6 |
| USB Charge Port | Yes |
| USB Charge Port Amperage | 2.4 A (Shared) |
| USB Charge Port Quantity | 2 |
| USB Charge Port Type | 1 x Type A / 1 x Type C |
| USB Charge Port Voltage | 5 VDC |
| USB Charge Port Watts | 18 Watts |

P6WUC15

WALL-TAP SURGE PROTECTION

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING

| | |
|----------------------------|---------------------------|
| Attenuation | 32 dB |
| Clamping Voltage | 800V (H-N, H-G, N-G) |
| EMI/RFI Filtration | 150 KHz 100 MHz Yes |
| Maximum Surge Current | 45,000 A |
| Maximum Surge Current H-G | 15,000 A |
| Maximum Surge Current H-N | 15,000 A |
| Maximum Surge Current N-G | 15,000 A |
| Maximum Surge Voltage | 6000 V |
| Response Time | <1 Nanosecond |
| Surge Suppression (Joules) | 1800 J |

MANAGEMENT & COMMUNICATIONS

| | |
|----------------|---------------------------------------|
| LED Indicators | Protected (green) Grounded (green) |
|----------------|---------------------------------------|

PHYSICAL

| | |
|--------------------------|-------------|
| Color | White |
| Form Factor | Wall-tap |
| Form Factors Supported | Direct Plug |
| Material of Construction | Plastic |

PHYSICAL DIMENSIONS

| | |
|--|-----------------------|
| Physical Dimensions - Width/Height/Depth (cm) | 9.5 x 14.0 x 3.56 cm |
| Physical Dimensions - Width/Height/Depth (mm) | 95 x 140 x 36 mm |
| Physical Dimensions - Width/Height/Depth (in.) | 3.74 x 5.51 x 1.4 in. |
| Weight (kg) | 0.27 kg |
| Weight (lb) | 0.6 lbs. |

SHIPPING DIMENSIONS

| | |
|---|---------------------------|
| Shipping Dimensions - Width/Height/Depth (cm) | 11.51 x 16.51 x 6.1 cm |
| Shipping Dimensions - Width/Height/Depth (mm) | 115.06 x 165.1 x 60.96 mm |
| Shipping Dimensions - Width/Height/Depth (in) | 4.53 x 6.5 x 2.4 in. |
| Weight (kg) | 0.33 kg |
| Weight (lb) | 0.73 lbs. |

CERTIFICATIONS

| | |
|---------------|--|
| Environmental | RoHS Compliant |
| Safety | UL1449 UL498a DOE VI NRCan FCC ICES-003 |

WARRANTY

| | |
|-------------------------------|-------------------------|
| CEG Amount | \$100,000 |
| Connected Equipment Guarantee | Lifetime |
| Product Warranty | 1-Year Limited Warranty |