CyberPower

P205UCPDQB **DESKTOP CHARGER**

Protect home and office computers, electronics, and home theater equipment

The CyberPower P205UCPDQB brings you power, protection, and versatility - all in one compact unit. Featuring 2 AC power outlets with 1,500J of surge protection, 1 USB-A charging port, 1 USB-C PD charging port, and a 10W wireless Qi charging pad that works with iPhone and Android phones. It's perfect for desktops, tabletops or other high-traffic areas of the home or office.

TYPICAL APPLICATIONS

- Personal Electronics
- Wireless Speakers
- Cell Phones
- Tablets

- FEATURES
- Surge suppression: 1,500 J • Outlet type: NEMA 5-15R

- Outlet quantity: 2
- Total USB Output: 20W
- USB-C charge ports: 1
- USB-C charge output:
- 20W PD
- USB-A charge ports: 1 • USB-A charge output: 2.4A

- Wireless Charging: Qi 10W
- Power Cord Length: 5 ft
- Power cord type: braided
- Plug style: Right-angle 45° offset
- Volts: 125 V
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$100.000

SPECIFICATIONS

INPUT	
Circuit Breaker	None
Cord Length	5 ft (1.5 m)
Input Plug Type	NEMA 5-15R
Input Voltage	110-125 VAC
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset
OUTPUT	
Outlet Type	2 - NEMA 5-15R
Outlets - Total	2
USB Charge Port	Yes
USB Charge Port Amperage	2.4 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	1 Туре А, 1 Туре С
USB Charge Port Voltage	5 VDC

USB Charge Port Watts 20 Watts Yes Wireless Charging Wireless Charging Output 10 W Qi Certified Wireless Charging Type 600V (H-N, H-G, N-G) Clamping Voltage Coax Protection RG6 None EMI/RFI Filtration No Maximum Surge Current 15,000 A Maximum Surge Current H-G N/A 15,000 A Maximum Surge Current H-N Maximum Surge Current N-G N/A Maximum Surge Voltage 6,000 V Response Time <1 Nanosecond Surge Suppression (Joules) 1,500 J

SPECIFICATIONS CONT.

PHYSICAL	
Color	Black
Form Factors Supported	Horizontal Mount in Variety of Other Applications
Material of Construction	Plastic
PHYSICAL DIMENSIONS	
Physical Dimensions - WxHxD (cm)	8.41 x 4.29 x 8.41 cm
Physical Dimensions - WxHxD (mm)	84 x 43 x 84 mm
Physical Dimensions - WxHxD (in.)	3.31 x 1.69 x 3.31 in.
Weight (kg)	0.54 kg
Weight (lb)	1.20 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - WxHxD (cm)	13.34 x 16.26 x 8.38 cm
Shipping Dimensions - WxHxD (mm)	133.35 x 162.56 x 83.82 mm
Shipping Dimensions - WxHxD (in)	5.25 x 6.4 x 3.3 in.
Weight (kg)	0.68 kg
Weight (lb)	1.50 lbs.

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1449 UL2738 UL1310 FCC cUL DOE VI
WARRANTY	
CEG Amount	\$1,000,000
Connected Equipment Guarantee	Lifetime
Product Warranty	One-Year Limited