

Ultra Low Odor Waterbased Finish

Ultra Low Odor Waterbased Finish is a leading one-component athletic wood floor finish that is easy to use and easy to maintain with solid performance.

Features & Benefits

- Enhances natural appearance
- Clear translucent color prevents discoloration over wood and paint lines
- Excellent durability, built to deliver superior scruff and scratch resistance, even in high traffic environments
- Non-yellowing formula stays clear even after multiple recoats
- Maximum VOC content of 145 g/L

Applications

- For use on wood floors
- Designed to work in conjunction with:
 - Prominence^{TM/MC} Heavy Duty Floor Cleaner
 - Bona SuperCourt[®] Cleaner Concentrate
 - Bona SuperCourt[®] Cleaner Winter Formula







Ultra Low Odor Waterbased Finish

Use instructions

RECOATING:

- 1. Evaluate the floor Evaluate the entire wood floor for scuff marks, current finish condition/peeling, cupping and other damage, and overall floor appearance.
- Prepare the floor Gather all recommended tools and materials for the job. Secure the work area and post signs on entrance doors with "Do Not Enter." Use the Bona SuperCourt Microfiber Dusting Pad to dry dust the floor. Remove tape/sticky spots from the floor by cleaning with an auto scrubber and SuperCourt AFC Microfiber Cleaning Pads and Bona SuperCourt Cleaner Concentrate. Let dry.
- 3. Abrasion Once the floor has dried, abrade the floor using the Bona FlexiSand DCS Buffer and Bona DCS Back Vac with 180-grit Bona Diamond abrasives on a Bona MultiDisc. Abrade the entire work area. Work in sections, making sure to overlap sections. (Bona Diamond abrasives will last 4000-6000 square feet before replacement.)
- 4. Post-abrasion cleaning Vacuum and dry tack the entire floor to remove abrasive dust. Auto scrub or wet tack entire floor.
- 5. Coating preparation Before coating, tape-off floor plates, outlets, and areas needing protection from the floor finish. Strain finish and pour into clean dispensing container, or work from pail. Clean and rinse applicators. Place a Bona SuperCourt Ultra Low Odor finish pail every 2500 square feet to assist with coverage rate. Have an exit strategy. For more information, and to watch a video on the recoat process: visit www.Bona.com.

MIXING INSTRUCTIONS: Remove lid and stir thoroughly before using.

FINISHING:

- 1. Pour a 4" 6" wide line of finish along the starting wall. Go with the grain of the wood.
- 2. Using a clean, pre-dampened applicator; draw the applicator forward, with the grain of the wood, moving the finish toward the opposite wall. Hold the applicator at a "snowplow" angle will help maintain a wet edge at all times.
- 3. At the end of each run, turn the applicator and pull it toward you through the puddle and pad out the applicator parallel to the wet edge.
- 4. Feather out all turns. Do not push too hard or too fast to avoid dripping or splattering.
- 5. Missed areas can be touched up if seen right away.
- 6. BE SURE YOU ARE USING THE RECOMMENDED COVERAGE OF 500-600 SQUARE FEET PER GALLON. DO NOT SPREAD TOO THIN. BE SURE TO ESTIMATE THE RIGHT AMOUNT OF FINISH FOR THE JOB IN ORDER TO MINIMIZE THE DISPOSAL OF EXCESS PRODUCT.
- 7. Allow your first coat to dry 2-3 hours. High humidity and/or low temperature conditions will extend the drying time while increased ventilation and airflow will reduce dry time (recommended conditions of 65-80°F (18-27°C), 40-60% relative humidity.
- 8. Allow final coat to dry at least 48 hours before use.

INTERCOAT ABRASION: It is not necessary to abrade between coats of Bona SuperCourt Ultra Low Odor unless more than 48 hours has passed since the previous coat was applied. For smoothest results, abrade between all coats as necessary with Bona Conditioning Pads or a Bona MultiDisc and 240-grit Bona Diamond Abrasives.

CURING: The curing process takes approximately 7 days, (70% cured in 24 hours, 90% after 72 hours). Do not replace area rugs until the floor has fully cured. The floor may be walked on after 24 hours, but remains susceptible to scuffing or marring until completely cured. No wet cleaning during the first week, only dry dust with a Bona SuperCourt Microfiber Dusting Pad. (Do not use dry dust mop treatment chemicals on wooden floors).

Technical data	Ultra Low Odor Waterbased Finish
Certifications	GREENGUARD, MFMA
Color/Form	Milky White Liquid
рН	8.0
Scent	Slight Sweet
Shelf Life	1 year

Product	Pack size	Dilution	Product code	
Bona SuperCourt® Ultra Low Odor	1 x 5 gallon / 18.9 L Container	Ready-to-Use	5142227	

Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at www.diversey.com or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate.