



4700 W. 160th St.
Cleveland, OH 44135
PH:800-321-9532
FX:800-321-9535
www.oatey.com

TECHNICAL SPECIFICATION

FLAME PROTECTOR



TECHNICAL SPECIFICATION: Oatey Flame Protector is a heat shield to protect studs, walls, floors and other surfaces from sparks or flame and is ideal to use with propane and MAPP gas torches for applications up to 2500° F. Flame Protector is made with Zoltek Pyron® Fibers, a non-asbestos flame retardant material.



PHYSICAL/CHEMICAL PROPERTIES

Size 9" x 12"
Maximum Torch Tip Temperature 2500° F

DIRECTIONS FOR USE

Place Flame Protector behind area to be soldered. For best results use with propane gas. Life and usage of Flame Protector may be prolonged by using unburned surface area. Do not use if material is burned through. If working in tight areas, double the fabric over for best results.

PRECAUTIONS

Read all cautions and directions carefully before using this product. Use Flame Protector in a well ventilated area. Do not use with air or acetylene torches or other oxygen enhanced torches, as excessive direct flame above 2500° F will burn through the fabric. KEEP OUT OF REACH OF CHILDREN.

Refer to Material Safety Data Sheet for more information.

COMMON APPLICATIONS

Oatey Flame Protector is a heat shield to protect studs, walls, floors and other surfaces from sparks or flame and is ideal to use with propane and MAPP gas torches for applications up to 2500° F.

Consult Oatey Technical Department for applications not specifically referenced above.

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
31400	9" x 12" Flame Protector - Bagged	5	4 lbs.