

# 3M™ PELTOR™ Electronic Earplug, EEP-100

### **Product Description**





The 3M<sup>TM</sup> PELTOR<sup>TM</sup> Electronic Earplug helps protect your hearing, and can help improve situational awareness and communications in challenging environments.

The earpieces are rechargeable via a USB port on the charging case. The case also provides easy and convenient storage of the earpieces when not being used. The small and lightweight design helps improve the overall comfort and user experience, and can be used in combination with other 3M Personal Safety Equipment (PPE), such as helmets and face shields.

### **Key Features**

- Helps provide hearing protection
- Level-dependent function (for situational awareness)
- Intuitive one-button operation
- Rechargeable
- Durable storage and charging case (IP54)
- Small and lightweight design
- Compatible with most head borne 3M Personal Protective Equipment

## Common Applications

- Construction
- Maintenance
- Manufacturing
- Shooting

### Standards and Approvals

- Ingress Protection Rating: Earpieces and Case (with lid and USB port securely closed) are IP54 compliant.
- Noise Reduction Rating (NRR) tested in accordance with ANSI S3.19-1974

### Included

- 2 x Earplugs
- 1 x Charging case
- 2 × 3M<sup>™</sup> UltraFit<sup>™</sup> Communication Tips Replacement, Large
- 2 × 3M<sup>™</sup> UltraFit<sup>™</sup> Communication Tips Replacement, Medium
- 2 × 3M<sup>™</sup> UltraFit<sup>™</sup> Communication Tips Replacement, Small
- 2 × 3M<sup>™</sup> PELTOR<sup>™</sup> Communication Tip, Triple C
- 1 x USB cable
- 1 x User Instructions

### Models

Article Number	Description	3M ID
EEP-100	3M™ PELTOR™ Electronic Earplug, EEP-100	70071730793

## **Accessories and Spare Parts**

Article Number	Description	зм ір			
TEP-CORD	3M <sup>™</sup> PELTOR <sup>™</sup> Tactical Earplug Replacement Cord	70071673795			
370-TEPL-25	3M™ UltraFit™ Communication Tips 70071673746 Replacement, Large, 25 pairs				
370-TEPM-25	3M <sup>™</sup> UltraFit <sup>™</sup> Communication Tips Replacement, Medium, 25 pairs	70071673738			
370-TEPS-25	3M <sup>™</sup> UltraFit <sup>™</sup> Communication Tips Replacement, Small, 25 pairs	70071673720			
370-1019-10	3M <sup>™</sup> Skull Screws <sup>™</sup> , Communication Tips, 10 pairs	70071615275			
CCC-GRM-25	3M <sup>™</sup> PELTOR <sup>™</sup> Communication Tip, Triple C, 25 pairs	70071675212			
TEP-WINDSCREEN	3M™ PELTOR™ TEP/LEP WINDSCREEN FOAM	70071675907			

# **Technical Data Specifications**

Model	
Microphone Type:	Omni-directional

Earplug Power/Electrical	Earplug Power/Electrical Characteristics					
Earplug Battery Type: Lithium Ion						
Earplug Battery Life:	Up to 16 hours					
Earplug Battery Charge Time:	Approximately 180 minutes					
Earplug Volume Steps:	3 steps, Low, Normal, High					
Case USB Type:	Micro B					

Standards	
Ingress Protection Rating:	Complies with IP54 with cover and USB port closed.
NRR:	Tested in accordance with ANSI S3.19-1974

Physical Characteristics	Physical Characteristics						
Case Size (L x W x H):	89.6 mm x 61.6 mm x 27.3 mm						
Case Material:	ABS						
Earplug Keypad:	One button operation (On / Off / Volume Selection)						
RoHS Compliance:	RoHS II						
Weight Box containing charger, 2 Earplugs, 4 pair communications Eartips, USB cable:	8.46 oz						
Weight Charger:	2.01 oz						
Weight: 1 earpiece:	0.13m oz						

Environmental Character	Environmental Characteristics						
Storage temp range:							
1 Year:	-4 °F to 68 °F (-20 °C to 20 °C)						
3 Month:	-4 °F to 113 °F (-20 °C to 45 °C)						
1 Month:	-4 °F to 140 °F (-20 °C to 60 °C)						
Earpiece Operating temperature:	-4 °F to 122 °F (-20 °C to 50 °C)						
Charger Operating temperature:	32 °F to 113 °F (0 °C to 45 °C)						

### **Laboratory Attenuation**

Research suggests that users may receive less noise reduction than indicated by the attenuation value(s) on the packaging, due to variation in fit, fitting skill, and motivation of the user. Refer to your applicable regulations for guidance on how to adjust label values and estimate attenuation. In addition, 3M strongly recommends fit testing of hearing protectors.

**Table 1:** 3M<sup>™</sup> UltraFit<sup>™</sup> Eartips

	125	250	500	1000	2000	3150	4000	6300	8000	NRR	
Mean	36.2	33.7	34.7	32.0	34.5	37.4	35.6	38.0	37.5	23 dB	AL
	5.1	5.2	5.5	3.9	3.4	5.3	6.5	4.4	5.4		

**Table 2:** 3M<sup>™</sup> Triple-C Communication Eartips

	125	250	500	1000	2000	3150	4000	6300	8000	NRR	
Mean	34.5	30.6	36.3	35.2	35.5	38.6	37.6	44.6	45.7	27 dB	AL
	4.2	3.9	4.1	3.0	3.5	3.3	3.8	3.6	4.3		

**Table 3:** 3M<sup>™</sup> Skull Screws<sup>™</sup> Eartips (not included)

	125	250	500	1000	2000	3150	4000	6300	8000	NRR	
Mean	36.3	35.7	39.8	41.4	40.4	43.0	41.9	48.2	46.0	30 dB	AL
	5.3	5.5	5.5	4.2	3.4	4.6	3.5	4.6	4.2		

## **↑** CAUTION

When worn according to the User Instructions, these hearing protectors help reduce exposure to both continuous noises, such as industrial noises and noises from vehicles and aircraft, as well as very loud impulse noises, such as gunfire. It is difficult to predict the required and/or actual hearing protection obtained during exposure to impulse noises. For gunfire, the weapon type, number of rounds fired, proper selection, fit and use of hearing protection, proper care of hearing protection, and other variables will impact performance. To learn more about hearing protection for impulse noise, visit www.3M.com/hearing.

### ♠ WARNING

**Hearing Protection Products\*** These hearing protectors help reduce exposure to hazardous noise and other loud sounds. **Misuse or failure to wear hearing protectors at all times that you are exposed to noise may result in hearing loss or injury**. For proper use, see supervisor, User instructions, or call 3M Technical Service in the U.S.A at 1-800-243-4630. If there is any drainage from your ear or you have an ear infection, consult with your physician before wearing earplugs. Failure to do so may result in hearing loss or injury. Choking Hazard - Keep away from infants and small children.

### Warranty and Important Notice

Warranty

The warranty does not cover any damage caused by neglected maintenance or careless handling. For more information on maintenance, please see the user instruction. For complete warranty condition, contact your dealer or local 3M office.

Important Notice

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The User is responsible for determining the suitability of the products for their intended use. 3M acknowledges the respective Trademark Owners' rights in this literature.



Personal Safety Division 3M Center, Building 235-2W-70 St. Paul, MN 55144-1000

3M PSD products are occupational use only.

3M Canada P.O. Box 5757 London, Ontario N6A 4T1 In United States of America
Technical Service 1-800-665-2942
Web: www.3M.com/PELTOR
Email: PELTOR.comms@mmm.com

In Canada

Technical Service 1-855-484-3093 Customer Service 1-800-364-3577 Email: PELTOR.comms.canada@mmm.com 3M and PELTOR are trademarks of 3M Company and its affiliates, used under license in Canada. 3M acknowledges the respective Trademark Owners' rights in this literature. Please recycle. Printed in LISA.

© 2024, 3M. All rights reserved.