

AF-PL™

DESCRIPTION

AF-PL™ is specially formulated to effectively dissolve and remove grease, oil and other contaminants where plastics and rubber-like compounds are present.

- Quick acting
- Penetrates and displaces moisture
- Effectively cuts through and removes grease, oil, paint, ink, glue, adhesive, wax, dirt and grime
- Fast evaporation
- Residue-free
- Safe on plastics and rubber-like compounds
- Free of chlorinated solvents, CFC and HCFC
- Aerosol: strong jet blasts away contaminants

APPLICATIONS

Use AF- PL™ for:

- Cleaning of metal parts in presence of plastic or gaskets
- Maintenance, repair and overhaul of motors, machinery, vehicles and equipment
- Removal of glue, paint, ink, resin, sealant and flux residue
- Cleaning of electric components, instruments, lenses, glass, chains, gears, cables, etc...

RECOMMENDATIONS FOR USE

- Spray directly on parts

TECHNICAL DATA

Physical state: Typical odor, colorless

Density: 0.702g/mL (20°C/ 68°F)

VOC: 100% (w/w)

Flash point: -7°C (19.4°F)

Engineering controls: Ensure adequate ventilation

Incompatible substances: Oxidizing agents

Storage: Store below 50°C/122°F.

Shelf life: 2 years in closed container, stored in ideal conditions

ORDERING INFORMATION

Description	Size	Order No.	(M)SDS
Trigger sprayer	500ml	53-C 553	L-65
Liquid	5 L	53-C 556	L-65
Liquid	20 L	53-C 557	L-65
Liquid	200 L	53-C 558	L-65

Accessories

Air Force PL refillable sprayer	53-M 101
Industrial pump sprayer	53-L 120
Spout 20L pail	53-L 208
Spout 200L drum (3/4")	53-L 210
Valve for 200L drum (2")	53-L 209

(M) SDS available upon request or visit our web site at www.walter.com

Not for product specification. The technical data contained herein is intended as reference only and may change without notice.

Walter Surface Technologies Inc.

5977 Trans-Canada Highway, Pointe-Claire, Quebec H9R 1C1

Tel: 1-800-592-5837 or (514)630-2800 / Fax: (514)630-2825