

FROGTAPE™ PRO GRADE DECK AND JOIST FLASHING TAPE

TYPICAL APPLICATIONS

- For deck joist, ledger board, post and stair stringer flashing
- Also for sealing the following transitions: sill plate, wall to roof, deck to wall joints

PRODUCT FEATURES

- Excellent conformability for bending around edges and corners
- Wide installation temperature range from 0 F (-18 C) to 150 F (65 C), with long-term performance after install in temperatures ranging from -40 F (-40 C) to 240 F (115 C)
- Fast and easy install with no liner and no primers required
- Self-healing around nails and protrusions for a waterproof seal
- Protects decking components such as the deck joists, stair stringer, posts, and ledger board from water penetration
- All-weather performance with 12-month UV resistance
- Initially repositionable adhesion to a range of substrates, including challenging building materials such as pressure-treated wood, OSB, concrete and more
- Meets AAMA 711-22

CONSTRUCTION

Backing: 8.0 mils black polyolefin film

Adhesive: 5.0 mils solventless acrylic adhesive

Liner: Self-wound

STANDARD WIDTHS

1.89 in; 3.78 in; 6 in; 12 in
48 mm; 96 mm; 152 mm; 304.8 mm

STANDARD LENGTH

50 ft
15.3 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

AAMA 711-22

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 18 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil and/or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Anodized Aluminum	>1.5 lbs/in width	>0.26 N/mm
Adhesion to Exterior Glass Faced Gypsum	>1.5 lbs/in width	>0.26 N/mm
Adhesion to OSB	>1.5 lbs/in width	>0.26 N/mm
Adhesion to Plywood	>1.5 lbs/in width	>0.26 N/mm
Adhesion to Rigid PVC	>1.5 lbs/in width	>0.26 N/mm
Application Temperature Range	0 F to 150 F	-18 C to 65 C
MD Tensile Strength	18.5 lbs/in width	32.4 N/10 mm
Service Temperature Range	-40 F to 240 F	-40 C to 115 C
Thickness - Without Liner	13.0 mils	0.33 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies, or Shurtape Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

