

# Holds securely for a clean finish.

## 3M<sup>™</sup> Tapes for Hard-to-Bond Surfaces

with 3M<sup>™</sup> High-Strength Acrylic Adhesive 300LSE

Plastic to metal. Rubber to plastic. Even foam to chrome. Open your mind to new materials and new design possibilities.

Expect performance. Spec 3M.

Baby Care A White \_\_\_\_\_\_ Bio Care \_\_\_\_\_\_ Hand Wash \_\_\_\_

/Wool


Spin

7kg

## Thin can stick to hard-to-bond surfaces.

Tapes engineered with 3M<sup>™</sup> High-Strength Acrylic Adhesive 300LSE have superpowers. They hold securely and perform reliably — giving you more freedom to imagine. To design. To build.

- High initial bond strength to low surface energy substrates
- High shear strength to low surface energy substrates
- Good anti-lifting properties on flat and curved surfaces
- Double coated tape is easy to die-cut, handle and apply



### Hard-to-bond materials:

- ► ABS Plastic
- Aluminum with Nylon Coating
- Coated Paper
- ► EPDM Rubber
- ► Foam
- ► Graphite

- ► Metal Mesh
- ► Painted Surfaces
- ► PET Film
- ► Polycarbonate with Coating
- Polypropylene
- Powder-Coated Surfaces

Printed Metal

No need for primer

- Rubber Polyurethane
- ► SIS Rubber
- ► Wood


## Make unstickable materials stickable in many markets.



## Adhesives engineered for your application.

3M<sup>™</sup> High Performance Acrylic Adhesive 200MP, used in products such as 467MP, has a proven record for reliable bonding to common substrates, including metal and glass (high surface energy substrates).

Now, to adhere to **hard-to-bond surfaces**, such as various plastics (low surface energy substrates), **3M<sup>™</sup> High Strength Acrylic Adhesive 300LSE is your #1 choice**.



### 3M<sup>™</sup> Tapes for Hard-to-Bond Surfaces

Tape Thickness (mm)	Product	Adhesive Type	Carrier	Liner Type	Color
0.05	3M <sup>™</sup> Double Coated Tape 93005LE*	3M <sup>™</sup> High-Strength Acrylic Adhesive 300LSE	PET	PCK #58, PCK #83	Clear
0.05	3M <sup>™</sup> Double Coated Tape 93005LEB		PET	PCK #58, PCK #83	Black
0.06	3M <sup>™</sup> Adhesive Transfer Tape 9471LE*		-	PCK #58	Clear
0.06	3M <sup>™</sup> Adhesive Transfer Tape 9671LE		-	PCK #83	Clear
0.10	3M <sup>™</sup> Double Coated Tape 93010LE		PET	PCK #58	Clear
0.13	3M <sup>™</sup> Adhesive Transfer Tape 9472LE*		-	PCK #58	Clear
0.13	3M <sup>™</sup> Adhesive Transfer Tape 9672LE		-	PCK #83	Clear
0.15	3M <sup>™</sup> Double Coated Tape 93015LE*		PET	PCK #58	Clear
0.17	3M <sup>™</sup> Double Coated Tape 9495LE		PET	PCK #58	Clear
0.20	3M <sup>™</sup> Double Coated Tape 93020LE		PET	PCK #58	Clear

\*Recommended key products.



#### Solventless technology

3M<sup>™</sup> High-Strength Acrylic Adhesive 300LSE is made with a solventless technology.



Industrial Adhesives and Tapes Division 3M Center, Building 225-3S-06 St. Paul, MN 55144

Phone 800-362-3550 Web 3M.com/converter **Product Use:** All statements, technical information and data contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty, Limited Remedy, and Disclaimer: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. User is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

© 3M 2017. All rights reserved. 3M is a trademark of 3M Company. 3M is a Responsible Tape Manufacturer, PSTC. Printed in U.S.A.