

**NEW**

# BLENDIX™ FLAP DISC

The longest life & highest overall material removal



**WALTER**

Achieve Greatness™

# BLENDEX FLAP DISCS

WALTER's Blendex™ flap discs combine the aggressive material removal of a flap disc with the smooth finish and versatility of a surface conditioning disc. This allows for more consistent results, while reducing operator downtime to switch discs. These flap discs are built with WALTER's Eco-Trim™ trimmable backing, extending the life of the product up to three times, as well as MAX-LIFE™ cold curing glue to maximize the abrasive grain's freshness!



| Diameter | Arbor | Grade    | Order No. | Max RPM | Std. Pkg. | Std. Ctn. |
|----------|-------|----------|-----------|---------|-----------|-----------|
| 4.5"     | 7/8"  | X-Coarse | 15-I 454  | 13,300  | 10        | 40        |
| 4.5"     | 7/8"  | Coarse   | 15-I 458  | 13,300  | 10        | 40        |
| 4.5"     | 7/8"  | Medium   | 15-I 468  | 13,300  | 10        | 40        |
| 4.5"     | 7/8"  | Fine     | 15-I 478  | 13,300  | 10        | 40        |
| 5"       | 7/8"  | X-Coarse | 15-I 504  | 12,200  | 10        | 40        |
| 5"       | 7/8"  | Coarse   | 15-I 508  | 12,200  | 10        | 40        |
| 5"       | 7/8"  | Medium   | 15-I 518  | 12,200  | 10        | 40        |
| 5"       | 7/8"  | Fine     | 15-I 528  | 12,200  | 10        | 40        |



**FOR MORE INFORMATION, TO SCHEDULE A FREE DEMO OR TO ORDER:**

**United States:**

Phone: (800) 522-0321 | Fax (866) 274-4435  
Email: OrderDesk.US@walter.com

**Canada:**

Phone: (888) 592-5837 | Fax (866) 581-1121  
Email: csr@walter.com



## FEATURES

- ▶ Combines woven nylon with aggressive grain blends for the most consistent results
- ▶ Eco-Trim™ trimmable backing extends product life up to three times
- ▶ Flexible backing allows for better operator comfort
- ▶ MAX-LIFE™ Glue ensures the freshest abrasives possible to avoid micro-cracking and drying out, which improves consistency and can extend disc life by up to 25%

**PRO TIP:** Extend up to 3 times the life of your flap disc: when the flaps overhang wears down, trim away 1/4" of the backing at a time to expose fresh abrasive grains.

Available at:

WALTER Surface Technologies Inc. © 2024 All Rights Reserved. WALTER Surface Technologies and Bio-Circle logos are trademarks or registered trademarks of WALTER Surface Technologies Inc. Other company, product or service names may be trademarks or service marks of WALTER Surface Technologies or others. 98-E 179 (04-24)