

CyberPower

B602RC1BK

ESSENTIAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower B602RC1BK surge protector offers vital protection for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges from reaching and potetially harming your electronic equipment. The B602RC1BK provides 500 joules of protection with six outlets and a two-foot power cord. Features of the B602RC1BK include automatic shutdown, metal oxide varistor (MOV) technology, keyhole mounting slots, and an impact-resistant casing. This surge protector comes with a Limited Lifetime Warranty and a \$25,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- Surge Suppression: 500 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5 to 15P
- Plug style: Straight
- Outlet type: 6 NEMA 5 to 15R (surge-protected)
- Power cord: 2 ft.
- Model Color: Black
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$25,000



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	2 ft. (0.6 m)
Input Plug Type	NEMA 5 to 15P
Plug Style	Straight
OUTPUT	
Outlet Type	6 NEMA 5 to 15R
Outlets - Total	6

SURGE PROTECTION & FILTERING	
Clamping Voltage	800V (H-N)
Maximum Surge Current	15,000 A
Maximum Surge Current H-N	15,000 A
Response Time	<1 Nanosecond
Surge Suppression (Joules)	500 J
PHYSICAL	
Color	Black
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)

B602RC1BK

ESSENTIAL SURGE PROTECTOR

SPECIFICATIONS - CONTINUED

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	4.55 cm, 3.61 cm, 24.77 cm
Physical Dimensions - Width/Height/Depth (mm)	45 mm, 36 mm, 248 mm
Physical Dimensions - Width/Height/Depth (in.)	1.79 in., 1.42 in., 9.75 in.
Weight (kg)	0.24 kg
Weight (lbs.)	0.53 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	7.01 cm, 3.61 cm, 27.79 cm
Shipping Dimensions - Width/Height/Depth (mm)	70.1 mm, 36.07 mm, 277.88 mm
Shipping Dimensions - Width/Height/Depth (in.)	2.76 in., 1.42 in., 10.94 in.
Shipping Weight (kg)	0.25 kg
Shipping Weight (lbs.)	0.55 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1363, 1449
WARRANTY	
CEG Amount	\$25,000
Connected Equipment Guarantee	Lifetime
Product Warranty	Limited Lifetime