## SPECIFICATION SUBMITTAL SHEET

jones stephens corporation


LOG LIGHTER VALVES
WITH T-BURNERS


Feet





## features and benefits:

- Solid brass escutcheon, 1/4" key and close nipple orifice included
- Individually tested (pressure test open and closed after installation)
- Angle: 188,000 BTU / Straight: 120,000









PART NO.	DESCRIPTION	Α	В	С	D	E	
□ L75-406	CP angle natural gas	12 <sup>1</sup> /4"	1 <sup>1</sup> /4"	1 <sup>1</sup> /2"	2 <sup>1</sup> /4"	23/4"	
□ L75-407	PB angle natural gas	12 <sup>1</sup> /4"	1 <sup>1</sup> /4"	1 <sup>1</sup> /2"	2 1/4"	$2^{3}/4''$	
□ L75-408	CP straight natural gas	12 <sup>1</sup> /4"	1 <sup>1</sup> /4"	1 1/2"	2 1/4"	-	
□ L75-409	PB straight natural gas	12 <sup>1</sup> /4"	1 <sup>1</sup> /4"	1 1/2"	2 1/4"	23/4"	
□ L75-400	CP angle LPG	12 <sup>1</sup> /4"	1 <sup>1</sup> /4"	1 1/2"	2 1/4"	4"	
□ L75-401	PB angle LPG	12 <sup>1</sup> /4"	1 <sup>1</sup> /4"	1 1/2"	2 1/4"	23/4"	
□ L75-402	CP straight LPG	12 <sup>1</sup> /4"	1 <sup>1</sup> /4"	1 1/2"	2 1/4"	23/4"	
□ L75-403	PB straight LPG	12 <sup>1</sup> /4"	1 <sup>1</sup> /4"	1 1/2"	2 1/4"	23/4"	

PART NO.	F	G	Н	I	J	K	L
□ L75-406	1 <sup>1</sup> /4"	2"	3 3/4"	3″	1/2"	-	-
□ L75-407	1 <sup>1</sup> /4"	2″	3 3/4"	3″	1/2"	-	-
□ L75-408	1 <sup>1</sup> /4"	2"	3 3/4"	3″	1/2"	4"	2 1/2"
□ L75-409	1 <sup>1</sup> /4"	2″	3 3/4"	3″	1/2"	3 3/4"	2 <sup>5</sup> /8"
□ L75-400	1 <sup>1</sup> /4"	2"	3 3/4"	3″	1/2"	-	-
□ L75-401	1 <sup>1</sup> /4"	2″	3 3/4"	3″	1/2"	-	-
□ L75-402	1 <sup>1</sup> /4"	2″	3 3/4"	3″	1/2"	4"	2 <sup>5</sup> /8"
□ L75-403	1 <sup>1</sup> /4"	2″	3 3/4"	3″	1/2"	4"	2 <sup>5</sup> /8"