# **CWH SERIES ARCHITECTURAL SMALL WALL HEATERS**

### COMMERCIAL FAN-FORCED WALL HEATER



#### **IDEAL SPACES**

- Vestibules
- Entrance Ways
- Lobbies
- Hallways
- Stairwells
- Restaurants
- Conference Rooms
- Offices
- Basements
- Family Rooms
- Bedrooms

#### **COLORS**

Statuary Bronze

#### **DIMENSIONS**

- Grille: 12-1/8"H x 10-5/8"W x 1"D
- Back Box: 11"H x 9-1/4"W x 4"D

#### **TEMP RANGE**

■ 40°- 90°F

#### **CFM**

**65** 









- Contemporary bar-stock grille designed to provide optimized airflow
- Automatic fan delay eliminates cold drafts on start-up and discharges residual heat from the heater body during shut down
- Manual reset thermal overheat protector disconnects power in the event of accidental blockage
- All units have a permanently lubricated enclosed fan motor, which creates long life and low maintenance, and gently distributes warmth throughout the area
- Built-in power on/off switch for added safety during maintenance and built in tamper-resistant thermostat
- Tamper-proof plug for thermostat hole



# **CWH SERIES ARCHITECTURAL SMALL WALL HEATERS**

# COMMERCIAL FAN-FORCED WALL HEATER

MODELS & SPECIFICATIONS								
CATALOG NO.	UPC	VOLTS	WATTS	AMPS	PHASES	BTU/HR.	SHIP WT. (LBS.)	
CWH1101DSAF	6 85360 16296 6	120	1000	8.4	1	3413	12	
			500	4.2	1	1706	12	
CWH1151DSAF	6 85360 16298 0	120	1500	12.5	1	5120	12	
			750	6.25	1	2560	12	
CWH1201DSAF	6 85360 16302 4	120	1800	15	1	6143	12	
CWH1202DSAF	6 85360 16306 2	240	2000	8.4	1	6826	12	
			1000	4.2	1	3413	12	
		208	1500	7.3	1	5120	12	
			750	3.61	1	2560	12	
CWH1207DSAF	6 85360 16308 6	277	2000	7.3	1	6826	12	
			1000	3.61	1	3413	12	
		240	1500	6.25	1	5120	12	
			750	3.2	1	2560	12	
CWH1157DSAF	6 85360 16300 0	277	1500	5.5	1	5120	12	
			750	2.75	1	2560	12	
		240	1125	4.7	1	3840	12	
			562	2.35	1	1920	12	
CWH1208DSAF	6 85360 16304 8	208	2000	9.6	1	6826	12	
			1000	4.8	1	3413	12	

ACCESSORIES							
CATALOG NO.	UPC	DESCRIPTION	SHIP WT. (LBS)				
CWHSMAG	6 85360 14852 6	Surface Mounting Frame (Accessory). Order separately. 12-1/2"H x 10-3/8"W x 4"D, Statuary Bronze	3				
CWHS1AG	6 85360 14853 3	1 in. Semi-Recess Mounting Frame, 12-1/2"H x 10-3/8"W x 1"D, Statuary Bronze	3				
CWHS2AG	6 85360 14854 0	2 in. Semi-Recess Mounting Frame, 12-1/2"H x 10-3/8"W x 2"D, Statuary Bronze	3				

NOTE: Factory-wired for higher wattage, field-convertible to half wattage. Do not install heater closer than 4 in. from floor. Do not install heater behind towel rack, behind door, in floor, in ceiling, in closet, or where air flow may be obstructed.







