

DS-72xxHUI-Kx(/P) Series

TurboHD DVR

TurboHD[™]



- H.265+/H.265/H.264+/H.264 and Dual-Stream Video Compression
- Supports HD-TVI and Analog Cameras
- Full Channel Recording up to 5 MP
- Full Channel 1080p Real-Time Recording
- HDMI and VGA Output up to 3840 x 2160
- Long Over-the-Coax Transmission Distance
- Up to 16-ch Synchronous Playback

Hikvision's TurboHD DS-72xxHUI-Kx and DS-72xxHUI-Kx/P Series DVRs feature a range of self-adaptive signal inputs and offer camera support on up to 16 channels. They offer transmission distances up to 2,630 ft (800 m) on 1080p, and 3,940 ft (1,200 m) on 720p HD-TVI. Hikvision's TurboHD DVRs also feature the latest H.265+ encoding technology, which improves recording efficiency and reduces data storage costs.

The DS-72xxHUI-Kx and DS-72xxHUI-Kx/P Series DVRs support advanced analytics such as line crossing, intrusion, and scene change detection.

Additionally, /P models support Power-over-Coax (PoC) technology.

Available models:


DS-7204HUI-K1: 4-channel
DS-7204HUI-K1/P: 4-channel, PoC
DS-7208HUI-K2: 8-channel
DS-7208HUI-K2/P: 8-channel, PoC
DS-7216HUI-K2: 16-channel
DS-7216HUI-K2/P: 16-channel, PoC

Specifications

| | DS-7204HUI-K1 | DS-7204HUI-K1/P | DS-7208HUI-K2 | DS-7208HUI-K2/P | DS-7216HUI-K2 | DS-7216HUI-K2/P |
|---------------------------|--|-----------------------|---|-----------------------|--|-----------------------|
| Video/Audio Input | | | | | | |
| Video Compression | H.265+/H.265/H.264+/H.264 | | | | | |
| Analog Video Input | 4-ch BNC interface (1.0 Vp-p, 75 Ω) | | 8-ch | | 16-ch | |
| HD-TVI Input | 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25 | | | | | |
| CVBS Input | PAL/NTSC | | | | | |
| PoC Camera Input | --- | Hikvision PoC cameras | --- | Hikvision PoC cameras | --- | Hikvision PoC cameras |
| | NOTE: Do not unplug or plug the PoC camera if it is powered by an external power supply. | | | | | |
| IP Video Input | 4-ch ¹ Up to 8 MP resolution Supports H.265+/H.265/H.264+/H.264 IP cameras | | 8-ch ² | | 16-ch ³ | |
| Audio Compression | G.711u | | | | | |
| Audio Input | 4-ch, RCA (2.0 Vp-p, 1K Ω) | | | | | |
| Video/Audio Output | | | | | | |
| CVBS Output | 1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: 704 × 480 | | | | | |
| HDMI/VGA Output | 1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz | | VGA: 1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz HDMI: 1-ch, 4K (3840 × 2160)/30 Hz, 2K (2560 × 1440)/60 Hz, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz | | | |
| Encoding Resolution | 5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF | | | | | |
| Frame Rate | Main stream: 8 MP @ 8 fps/5 MP @ 12 fps/4 MP @ 15 fps/3 MP @ 18 fps; 1080p/720p/WD1/4CIF/VGA/CIF @ 30 fps Sub-stream: WD1/4CIF/CIF @ 30 fps | | | | | |
| Video Bit Rate | 32 Kbps to 10 Mbps | | | | | |
| Audio Output | 1-ch, RCA (linear, 1K Ω) | | | | | |
| Audio Bit Rate | 64 Kbps | | | | | |
| Dual-Stream | Supported | | | | | |
| Stream Type | Video, video and audio | | | | | |
| Synchronous Playback | 4-ch | | 8-ch | | 16-ch | |
| Network Management | | | | | | |
| Remote Connections | 128 | | | | | |
| Network Protocols | TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF | | | | | |
| Hard Disk | | | | | | |
| SATA | 1 SATA interface | | 2 SATA interfaces | | | |
| Capacity | Up to 10 TB capacity for each disk | | | | | |
| External Interface | | | | | | |
| Two-Way Audio Input | 1-ch, RCA (2.0 Vp-p, 1K Ω) [using the first audio input] | | | | | |
| Network Interface | 1, RJ-45 10M/100M self-adaptive Ethernet interface | | | | 1, RJ-45 10M/100M/1000M self-adaptive Ethernet interface | |
| Serial Interface | RS-485 (half-duplex) | | | | | |
| USB Interface | 2 × USB 2.0 | | Front panel: 1 × USB 2.0; rear panel: 1 × USB 3.0 | | | |
| Alarm In/Out | 4/1 | | 8/4 | | 16/4 | |
| General | | | | | | |
| Power Supply | 12 VDC (non-PoC models), 48 VDC (PoC models) | | | | | |
| Consumption (w/o HDD) | ≤40 W | | ≤60 W | | ≤10 W | |
| Working Temperature | 14° to 131° F (-10° to 55° C) | | | | | |
| Working Humidity | 10% to 90% non-condensing | | | | | |
| Dimensions (W × D × H) | 12.4" × 9.5" × 1.8" (315 mm × 242 mm × 45 mm) | | 15" × 12.6" × 1.9" (380 mm × 320 mm × 48 mm) | | | |
| Weight (w/o HDD) | ≤2.6 lbs (1.16 kg) | | ≤3.9 lbs (1.78 kg) | | ≤4.4 lbs (2 kg) | |

Physical Interfaces

DS-7204HUI-K1(/P)



| | |
|-----------------------------|--|
| 1. Video In | 8. RS-485 Serial Interface |
| 2. Audio In, RCA Connector | 9. Power Input: 12 VDC (48 VDC for PoC models) |
| 3. Audio Out, RCA Connector | 10. Power Switch |
| 4. VGA Interface | 11. Gnd |
| 5. HDMI Interface | 12. Video Out |
| 6. USB Port | 13. Alarm In/Out |
| 7. LAN Network Interface | |

NOTE:

The DS-7208HUI-K2(/P) and DS-7216HUI-K2(/P) rear panels provide 8 and 16 video input interfaces, respectively

¹Up to 8 IP channels if Enhanced IP Mode is enabled and all analog channels are disabled. Enhanced IP Mode and Enhanced VCA Mode cannot run simultaneously.

²Up to 16 IP channels if Enhanced IP Mode is enabled and all analog channels are disabled. Enhanced IP Mode and Enhanced VCA Mode cannot run simultaneously.

³Up to 32 IP channels if Enhanced IP Mode is enabled and all analog channels are disabled. Enhanced IP Mode and Enhanced VCA Mode cannot run simultaneously.