

# PS 750



## HEAVY DUTY GRADE TENSILIZED STRAPPING TAPE

### TYPICAL APPLICATIONS

- For heavy duty strapping, bundling, banding, palletizing and reinforcing applications

### PRODUCT FEATURES

- Quick and aggressive bond to a variety of surfaces
- Abrasion-, moisture- and solvent-resistant
- Durable, high memory polypropylene film backing contracts when applied under firm manual tension

### CONSTRUCTION

Overall Grade/Function: Heavy duty

Backing: Tensilized, mono-oriented polypropylene film

Adhesive: Emulsion acrylic

### STANDARD WIDTH(S)

1 in

### STANDARD LENGTH(S)

60 yd

Contact your Shurtape sales representative for other available sizes

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



**CLEAR**  
(CLR)

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	145 lbs/in width	253.9 N/10 mm
Adhesion to Stainless Steel	45 oz/in width	4.93 N/10 mm
Thickness	5 mils	0.13 mm
Elongation	30%	30%
Service Temperature Range	0 F to 250 F	-18 C to 121 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

