CyberPower

MP92SS | ESSENTIAL SURGE PROTECTORS TWO-PACK

Protect home and office computers, electronics, and home theater equipment

The CyberPower MP92SS surge protector two-pack offers vital surge protection for common home and office electronics such as computers and peripherals, home theater equipment, and appliances. With 500 joules of surge protection, both units in the MP92SS prevent power surges and power spikes caused by storms and electrical grid fluctuations from reaching and potentially harming your valuable electronic equipment. Each surge protector in the MP92SS has six standard, grounded power outlets and a 3-foot braided power cord with a standard grounded plug.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- AC Outlets: 6
- AC Outlet Type: NEMA 5-15R
- Surge Protection: 500 Joules
- Cord Length: 3 ft
- · Cord Type: Braided
- Plug Type: NEMA 5-15P
- Electrical Rating: 125V/15A/60Hz
- Connected Equipment Guarantee: \$25,000
- Warranty: Lifetime Limited Warranty



SPECIFICATIONS

15 A
3 ft (0.9 m)
NEMA 5-15P
15 A
Straight
6 - NEMA 5-15R
6
125 VAC
1,875 W

SURGE PROTECTION AND	FILTERING
Attenuation	32 dB
Clamping Voltage	800V (H-N)
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	15,000 A
Maximum Surge Current H-N	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	500 J

MP92SS ESSENTIAL SURGE PROTECTORS TWO-PACK

SPECIFICATIONS CONT.

PHYSICAL	
Color	White
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Material of Construction	Plastic
DIMENSIONS	
Physical Dimensions - WxHxD (cm)	9.09 x 3.45 x 24.77 cm
Physical Dimensions - WxHxD (mm)	91 x 35 x 248 mm
Physical Dimensions - WxHxD (in)	1.79 x 1.36 x 9.75 in.
Physical Weight (kg)	0.24 kg
Physical Weight (lb)	0.54 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - WxHxD (cm)	13.97 x 27.31 x 8.89 cm
Shipping Dimensions - WxHxD (mm)	139.7 x 273.05 x 88.9 mm
Shipping Dimensions - WxHxD (in)	5.5 x 10.75 x 3.5 in.
Shipping Weight (kg)	0.57 kg
Shipping Weight (lbs.)	1.25 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Environmental Safety	RoHS Compliant UL1363, UL1449 4th Edition
	·
Safety	·
Safety WARRANTY	UL1363, UL1449 4th Edition