





While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or quarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

ECONOMY GRADE BOPP BOX SEALING TAPE AQUEOUS BASED ACRYLIC ADHESIVE • HAND ROLL

DESCRIPTION

This tape is made of polypropylene film coated with aqueous acrylic adhesive. Resistant to UV and perform under a wide temperature range. Excellent tear and impact resistance. This tape ages well and will not discolor. Available in clear only.

MAIN FEATURES

- Resistance to UV, moisture, cold and weathering.
- Good initial tack, long term adhesion.
- Perform under wide temperature range.
- Clarity: tape stays clear and won't yellow.
- Good strength and impact resistance.

APPLICATIONS

- Packaging, holding and bundling applications where moisture resistance is required.
- Performs well in cold environment (meat, food processing and dairy plants).
- Label protection, surface lamination.
- Single strip closure of regular slotted containers (RSC's) dispensed by hand held box sealer.
- Repair tears in boxes, bags, etc., while in transit or storage.

TECHNICAL DATA

Colour	
Backing	Bi-axially Oriented Polypropylene Film
	Aqueous Based Acrylic Adhesive
Thickness	1.6 mil
Adhesion to steel	18 oz/in
Tensile strength	15 lb/in
9	100%
	7°C (45°F) to 40°C (104°F)
Temperature Resistance	30°C (-22°F) to 54°C (130°F)