

Access II™ brings the classic aesthetic of sandstone to life through dynamic patterning. High-definition swathes of color shift across the tile for visual movement. Cool tones in a matte finish lend an approachable sense of modernity.

ACCESS II™

Glazed Porcelain



FLOOR / WALL  RESIDENTIAL  COMMERCIAL  INDOOR  OUTDOOR 



Path



Route



Tour



Voyage

Mosaics



Path







Route



Tour



Voyage

Sizes							
	24" x 47" 23.62" x 47.24"	12" x 24" 11.81" x 23.62"	12" x 12" Mesh 11.73" x 11.73"	3" x 12" Floor SBN			
Thickness	10mm	10mm	10mm	10mm			
Faces	4	16	N/A	N/A			
Finish	Matte	Matte	Matte	Matte			
Edge	Rectified	Rectified	Cut	Cut			
Grout Joint Recommendation	3/16"	3/16"	3/16"	3/16"			
Testing	Abrasion Resistance C1027	Breaking Strength C648	Chemical Resistance C650	Water Absorption C373	DCOF ANSI A1371	Scratch Hardness MOHS	Shade Variation Rating
	IV	≥425 lbf	Resistant	<0.5%	>0.50	6	V3

Product and Installation Details | ANSI A108.02
Section 4.3.8.2 - For running bond/brick jointing patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



 Sustainability Attributes

- Red List Free
- Health Product Declaration (HPD) provided upon request
- Product Packaging is 100% recyclable
- VOC Free

*For more information visit www.emser.com. Always consult a professional for proper usage and installation.