

INSTALLATION AND SAFETY INSTRUCTIONS

FOR YOUR SAFETY

WARNING: BE SURE THE ELECTRICITY TO THE WIRES YOU ARE WORKING ON IS SHUT OFF; EITHER THE FUSE IS REMOVED OR THE CIRCUIT BREAKER IS SHUT OFF.

GENERAL

You don't need special tools to install this fixture. Be sure to follow the steps in the order given. Under no circumstances should a fixture be hung on house electrical wires, nor should a swag type fixture be installed on a ceiling, which contains a radiant type heating system. Read instructions carefully. If you are unclear as to how to proceed, consult a qualified electrician.

NOTE: Proper wiring is essential for the safe operation of this fixture.

Fixture Assembly

Carefully remove the fixture from the carton and check that all parts are included as shown in figure. Be careful not to misplace any of the screws or parts, which are needed to install this fixture.

INSTALLATION

Step 1: Unscrew the ball nut (G) from the threaded rod (E). Adjust threaded rod (E) on mounting bracket (A) to allow fixture body (F) to rest flush against the ceiling when ball nut (G) is tightened. Secure the mounting bracket (A) to the outlet box (not included) through the outlet box screws (B).

Step 2: Pull out the source wires from the outlet box (not included). **Make wire connections with wire connectors (C) as follows:**
--Use the wire connector (C) to connect the white fixture wire to the white (neutral) supply wire from the outlet box (not included).
--Use the wire connector (C) to connect the black fixture wire to the black (live) supply wire from the outlet box (not included).
--Wrap the ground wire from the fixture body (F) around the ground screw (D) on the mounting bracket (A). Connect the ground wire from the fixture body (F) to the ground wire from the outlet box (not included), cover the connection with wire connector (C).

Step 3: Secure the fixture body (F) to the mounting bracket (A) through securing threaded rod (E) with the ball nut (G).

Step 4: Install the bulb (not included). Don't exceed the maximum capacity recommended on the fixture).

Step 5: Attach the glass (I) onto shade (K), Insert glass fix by tab.

Step 6: Attach the glass (J) onto shade (K), Insert glass fix by tab.

Step 6: Attach the shade (K) onto fixture body (F) using fixture screws (H).

CLEANING

To clean, wipe fixture with a soft and dry cloth. Do not use abrasive materials such as scouring pads or powders, steel wool or abrasive paper.

Line art shown may not exactly match the fixture enclosed. However, the installations do apply to this fixture.

