

PRO GRADE FLASHING AND WATERPROOFING TAPE



FROGTAPE PRO GRADE FLASHING AND WATERPROOFING TAPE



When it comes to challenging building envelope applications, you need a flashing and waterproofing tape that gets the job done right the first time.

Introducing FrogTape™ Pro Grade Flashing and Waterproofing Tape, a non-asphaltic, self-adhering tape that creates an airtight seal around windows and doors, and can also be used in weatherization applications around utility pipes, dryer vents and more.

Constructed with a high-strength film backing that conforms easily around building materials, along with a high-performance acrylic adhesive for all-weather performance, FrogTape Pro Grade Flashing and Waterproofing Tape delivers long-term performance, while saving you time and money on the job when it matters most.



Forms a strong bond to a wide variety of surfaces without primers, while remaining initially repositionable for clean and easy installation.



Durable and long-lasting with a 10-year warranty* so you can install with confidence.



Performs in a wide range of hot and cold climates. including extreme temperatures.



Self-healing around nails and protrusions for a waterproof seal. **APPLICATIONS**



UV Acrylic vs. Butyl Adhesive...what's the difference?

The ShurGRIP™ High-Performance Acrylic Adhesive used in the construction of FrogTape™ Pro Grade Flashing and Waterproofing Tape delivers several performance benefits compared to traditional butyl flashing tapes:

- Adhesive Technology: UV technology creates a stable adhesive system that won't break down over time, but rather creates a stronger bond
- Flexibility: Better performance and conformability across a range of hot and cold temperatures and climates
- Adhesion: Excellent adhesion to challenging building materials, including difficult-to-stick-to and rough • or uneven surfaces – with no primers required
- Workability: Initially repositionable during install to ensure the job is done right
- Performance: Improved compatibility with caulks and sealants
- **Sustainability:** A more sustainable manufacturing process without solvents, thermal ovens, air pollutants and greenhouse gasses - for a lasting, positive impact on our planet

High-strength, high-performance FrogTape Pro Grade Flashing and Waterproofing Tape features: Excellent conformability for bending around edges, corners and other building transitions Excellent adhesion to a range of substrates, including challenging building materials such as OSB, glass faced gypsum and concrete, via its ShurGRIP[™] high-performance acrylic adhesive Fast and easy install with no primers required Exclusive UV curing technology, so there's no volatile organic compounds (VOCs) and this tape won't react with caulks and sealants Wide installation temperature range from 0 F (-18 C) to 150 F (65 C), with long-term performance after install in temperatures ranging from -40 F (-40 C) to 240 F (115 C) Can be used as a Class II vapor retarder> 0.1 -1.0 perms Meets AAMA 711-22 Waterproofing







FrogTape™ Pro Grade Flashing Tape

Flashing tape for creating weatherproof seals around windows and doors in residential and commercial applications.



Item Number	Width	Length	Rolls/Case
105723	3.75 in	30 ft	12
105724	3.75 in	75 ft	12
105725	6 in	75 ft	8
105726	9 in	75 ft	4

FrogTape™ Pro Grade Flashing and Waterproofing Tape

Flashing tape for deck ledgers and waterproofing above grade construction applications.

Item Number	Width	Length	Rolls/Case
105727	12 in	50 ft	4



Physical Properties	Standard	Metric
MD Tensile Strength	16.3 lbs/in width	18.91 N/10 mm
CD Tensile Strength	5.7 lbs/in width	6.57 N/10 mm
Thickness	10 mils	0.254 mm
Service Temperature Range	-40 F to 240 F	-40 C to 116 C



FrogTape.com

©Shurtape Technologies, LLC 2024/MMC 00882