



## 3M™ Ethylene Oxide Monitors 3550, 3551

Thank you for choosing a 3M™ Diffusion Monitor. During this short review we will cover preparation and use of your monitor. For additional information, please consult your user instructions or contact 3M Technical Service at 1-800-243-4630.

Note that the 3M™ 3550 is an ethylene oxide monitor with pre paid analysis. The 3M™ 3551 is an ETO monitor without analysis included.

The diffusion monitor is a sampling device designed to measure average concentrations of certain contaminants over a measured time interval. The accuracy of the monitor meets OSHA requirements for 8 hour and 15 minute sampling. It is within +/- 25% at 0.5 to 2 ppm ethylene oxide.

The shelf life of the monitor is 18 months if stored in an area free of ethylene oxide. The expiration date is printed on a sticker on the can. It is a two digit month followed by a two digit year.



Click picture to start video. Click button to view video text

- ◆ This document has been encoded for a Windows operating system
- ◆ This version of the interactive document requires at minimum an internet connection with (256Kbs) minimum connection speed and Acrobat Reader 6.0 or higher for proper operation
- ◆ If there is no video, reaffirm that you are running Acrobat Reader 6.0 (minimum requirement)
- ◆ If video problems persist, try closing other applications that may be consuming the required memory
- ◆ If there is no audio or the volume is too low, right-click the audio setting icon and adjust accordingly
- ◆ Sound but no video, click NEXT



Click picture to start video.

Click button to view video text

3M™ Ethylene Oxide Monitor  
3550 and 3551



-Preparation and Use

Ethylene Oxide Monitor



3M™ Ethylene Oxide Monitor  
3550 and 3551



-Preparation for Shipment

Ethylene Oxide Monitor



3M™ Ethylene Oxide Monitor  
3550 and 3551



-Reading Report

Ethylene Oxide Monitor





### **WARNING**

**DO NOT USE FOR:**

- Ammonia, carbon monoxide, formaldehyde, hydrogen sulfide, isocyanates, methane, ethane, propane, methyl alcohol (methanol), methyl chloride, methyl, dimethyl, trimethyl amine, organic solids, sulfur dioxide.
- Reactive or polar compounds such as amines, phenols, aldehydes and low molecular weight alcohols.
- Extremely low concentrations within a sampling period of less than 8 hours.
- Particulates.

## **3M Occupational Health and Environmental Safety Division (OHESD)**

### **In the U.S. , contact:**

#### **Customer Service**

1-800-328-1667

#### **Technical Assistance**

1-800-243-4630

#### **Fax On Demand**

1-800-646-1655

#### **Internet**

<http://www.3M.com/occsafety>

#### **For other 3M Products**

1-800-3M-HELPS

### **In Canada, contact:**

3M Canada Company, OH & ESD

P.O. Box 5757

London, Ontario N6A 4T1

#### **Customer Service**

1-800-265-1840

#### **Technical Assistance (Canada Only)**

1-800-267-4414

#### **Fax On Demand**

1-800-646-1655

#### **Technical Assistance In Mexico**

01-800-712-0646

5270-2255, 5270-2119 (Mexico City only)

#### **Technical Assistance in Brazil**

0800-132333

#### **Fax On Demand O.U.S Locations**

1-651-732-6530

**3M Occupational Health and Environmental Safety Division  
3M Center, Building 235-2W-70  
St. Paul, MN 55144-1000**

© 3M January, 2008. All rights reserved.