

## CARE AND MAINTENANCE OF YOUR FAUCET

Your KINGSTON faucet has been finished to the most strict standards; however, due to the high content of minerals in the water, your finish may appear dull and tarnished after time. These are some do's and don'ts to maintain the luster on your faucet for many years to come.

#### $\Box$

- 1. Use a silicon based caulking when installing.
- 2. Clean your faucet with only a mild soap and water solution.
- 3. Dry your faucet after using it.
- 4. Give it a coat of Carnauba Wax periodically.

### DON'T


- 1. Use plumbers putty when installing the faucet.
- 2. Use any abrasive cleaning agents.


It may seem like a very simple and short list but it is that simple to maintain your faucet, looking shiny and new

If your faucet is already looking somewhat dull and tarnished, before replacing it, try cleaning it with a 50/50 solution of vinegar and water, you may need to soak some rags and wrap around those stubborn areas,

overnight and rinse completely in the morning, apply Carnauba wax once you have removed the mineral deposits.







## Parts:

<del> </del>		
Coupling Nut & Cone Washer	Lock Nut	Washer
1Pc	1Pc	1Pc

www.kingstonbrass.com

TOLL-FREE CUSTOMER SERVICE: 1-877-2-KBRASS TECHNICAL SUPPORT E-mail: service@kingstonbrass.com 12775 Reservoir Street, Chino, CA 91710




Failure to follow all directions may cause leaks which may result in water damage


# **KINGSTON** INSTALLATION INSTRUCTIONS **Water Filtration Faucet**

### BEFORE BEGINNING INSTALLATION:


- 1. Flush plumbing lines to clear any debris.
- 2. Shut off both supply lines after flushing.




1. Shut off hot and cold water supply under sink. Plug sink drain with cloth to avoid losing small parts. Remove old faucet.



3. Assemble the washers and lock nuts on the inlet shanks, and then tighten the nuts by hand.





2. Set the faucet in place, insert the inlet shanks through the sink holes, and press down.



4. Apply Teflon tape to threads on faucet shank and shut off valves, connect water supply line.

### **Need Tools:**






5. Turn on water supply valves and check for leaks, especially all supply line connections.

# Warning!!!

- Do not over-tighten nut during installation.
- Over-tighten may crack the valve and cause severe leak.



6. Turn on your filtration faucet and allow water to run for one minute to make sure installation set up completed.

Note: Aerator is attached to spout and not removable.



## **WARNING**

This filtration faucet is designed to be used solely to dispense cold water from a filtration water system, dispensing hot water or water not coming from a filtration water system may cause leaking and it could be hazardous to the user.