

PlumBite® Push On 90° Elbow Adapters

Specifications

- A heat-free method of joining Copper, CPVC, PE-RT or PEX tubing. Fittings can be removed and re-used, using the disassembly tool (sold separately).

Applications

- Commercial and residential potable and non-potable water applications

Materials

- Body-DZR Brass
- O-Ring- EPDM, Peroxide Cured
- Gripper Ring- Stainless Steel

Dimensions and Product Offering


Part Code	Part Code Bulk	A -Nominal (in.)	B -Nominal (in.)	C -(in.)	C -Tolerance +/- (in.)
C77431LF	-	1/2 FPT	1/2	1.26	0.07
C77432LF	-	1/2 MPT	1/2	1.27	0.07

Performance Specifications

- Maximum Temperature: 180°F
- Maximum Pressure: 200 PSI
- Service: Potable Water
- Exposure to water with elevated levels of inorganic materials (including but not limited to: Cl, Na, Mg, Ca, K), especially in high temperatures and high water velocity areas, could quicken the corrosion process.

Certifications/Listings/Approvals

- NSF/ANSI/CAN 61
- NSF/ANSI/CAN 372
- NSF/ANSI 14
- IAPMO listed
- IAPMO certified for use in manufactured joints without access panels
- ASSE 1061



Job Name _____
Location _____
Engineer _____
Contractor _____
Tag _____ PO# _____

