# **CyberPower**

# HT1206TCU HOME THEATER SURGE PROTECTORS

Protect home and office computers, electronics, and home theater equipment.

The Home Theater Surge Protector HT1206TCU provides 4500 joules of surge protection and 12 outlets to safeguard your home theater equipment from damage caused by electrical surges. The HT1206TCU also includes RJ11 ports for telecommunication devices such as phones, faxes, modems, and DSL lines. RG6 coaxial connectors protect cable/satellite TV receivers and broadband modems.

Features of the HT1206TCU include safe-fail (automatic shutdown), 12 surge-protected outlets (4 widely spaced for transformer plugs), a power cord (6 ft.), a right-angle plug with 45° off-set, LED status indicators, keyhole mounting slots, impact-resistant casing, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. This surge protector comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.



#### TYPICAL APPLICATIONS

- Office computers
- · Home theater

#### **FEATURES**

- 4500 Joule Surge Protection
- 125 Volts
- 12 x NEMA 5-15R Outlets
- Limited Lifetime Warranty
- \$350,000 CEG

#### **SPECIFICATIONS**

GENERAL		
Туре	Home Theater	
INPUT		
Voltage	125V	
Switch	Non lighted on/off - reset	
Plug Type	NEMA 5-15P	
Plug Style	Right angle, 45° offset to the right	
Circuit Breaker	15 A	
Cord Length	6 ft	
OUTPUT		
Outlet Type	NEMA 5-15R	
Outlets - Total	12	
Outlets - Widely Space	4	

OUTPUT - CONT.		
USB Charge Port - Total	2	
USB Charging Amperage	5 V @ 3.1 A (shared)	
SURGE PROTECTION & FILTERING		
Surge Suppression	4,500 joules	
Maximum Surge Current	H-N: 105,000 A; H-G: 30,000 A; N-G: 30,000 A	
Clamping Voltage	500V (H-N, H-G, N-G)	
Response Time	< 1 nanosecond	
EMI/RFI Filtration	150 kHz to 100MHz	
Attenuation	Up to 43 dB	
Phone Protection RJ11	1-In, 1-Out	
Coax Protection RG6	1-In, 1-Out	

## **HT1206TCU HOME THEATER SURGE PROTECTORS**



## **SPECIFICATIONS CONT.**

INDICATORS		
Lights	Protected (green) Grounded (green)	
PHYSICAL		
Form Factor	Strip	
Dimensions (WxHxD) (in)	4 x 11 x 1.5	
Weight (lbs.)	2	

CERTIFICATIONS		
Safety	UL1449, UL1363, UL1310, UL1283, UL497A, cUL	
Environmental	RoHS Compliant	
WARRANTY		
Product Warranty	Limited Lifetime Warranty	
Connected Equipment Guarantee	Lifetime	
CEG Amount	\$350,000	