

PRODUCTION GRADE BOX SEALING TAPE • HAND ROLL



DESCRIPTION

28 micron polypropylene film coated with 12% more high tack thermoplastic adhesive than # 243. Resistant to various chemicals and corrosion. Excellent tear and impact resistance. **00-clear, 04-tan up-charge. In USA only.

MAIN FEATURES

- Strength.
- High tack.
- Ease of application.
- Portable.
- Impact resistant.
- Water resistant.
- Tight unwind.

APPLICATIONS

- Packaging holding and bundling application where moisture resistance is required.
- Single Strips closure of regular slotted containers (RSC's) applied with a hand held dispenser.
- Screen masking.
- Repair tears in boxes, bags, etc., while in transit or storage.
- Label protection.

TECHNICAL DATA

Colour	Clear(00), Tan(04)
Backing	28 micron polypropylene film
Adhesive	Synthetic
Thickness	1.85 mil
Adhesion	32 oz/in
Tensile Strength.....	27 lb/in
Application Range.....	+7°C to 49°C (+45°F to 120°F)
Operating Range.....	-23°C to 60°C (-10°F to 140°F)

ADHESION

TENSILE STRENGTH

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.