

# RIDGID® RP 115 Press Tool




The new RIDGID® RP 115 gives professionals a more accessible option for press tools with major value. With single-handed jaw opening and operation, this tool is easy to use on residential jobs (and beyond). You can now press a vast majority of the fittings currently installed in the market with the latest from North America's leader in pressing.

- Mini: Smallest and lightest press tool on the market
- Agile: 210° head swivel for access to tight spaces
- Simple: One-handed jaw opening and operation for reach and ease of use
- Ergonomic: SlimGrip™ handle and optimized trigger for balance and control

## SPECIFICATIONS#

- Attachments ..... RIDGID Mini Series (see Order Information)
- Stroke Length ..... 1.26" (32 mm)
- Ram Force ..... 3,400 lbs. (15kN)

### Motor

- Voltage ..... 12V DC Rated
- Amperage ..... 2.0 A
- Power ..... 24 Watts
- Head Rotation ..... 210°
- Duty Cycle ..... 3 Press /min
- Power Supply ..... 12V Li-ion Rechargeable Battery Pack (RIDGID RB-1200 Series)

- Permissible Humidity ..... 80% maximum
- Operating Temperature Range ..... 15° F to 104° F (-10° C to 40° C)
- Storage Temperature ..... 32° F to 113° F (0° C to 45° C)
- Weight (no battery/ Attachment) ..... 2.9 lbs. (1.3 kg)
- Dimensions (no battery/ Attachment) ..... 13" x 4.5" x 2.5" (330 mm x 114 mm x 63 mm)
- Sound Pressure (L<sub>PA</sub>)\* ..... < 70 dB(A), K=3 dB(A)
- Vibration\* ..... < 2.5 m/s<sup>2</sup>, K=1.5

\* Sound and Vibration measurements are measured in accordance with a standardized test per Standard EN 62481-1.

- Vibration levels may be used for comparison with other tools and for preliminary assessment of exposure.

- Sound and vibration emissions may vary due to your location and specific use of these tools.

- Daily exposure levels for sound and vibration need to be evaluated for each application and appropriate safety measures taken when needed. Evaluation of exposure levels should consider the time a tool is switched OFF and not in use. This may significantly reduce the exposure level over the total working period.

# All specifications are nominal and may change as design improvements occur.



## ORDER INFORMATION

CATALOG NO.	MODEL NO.	DESCRIPTION	WEIGHT	
			(lb)	(kg)
72553	RP 115	Battery Kit with ProPress Jaws (1/2" – 3/4")	10.4	7.4
72578	—	1/2" Mini Jaw for ProPress	2.2	1
72583	—	3/4" Mini Jaw for ProPress	2.2	1

## ACCESSORIES

CATALOG NO.	MODEL NO.	DESCRIPTION
55183	—	12V Li-ion Batteries
55193	—	12V Charger
75338	—	Carrying Case



Viega® is a registered trademark of Viega GmbH & Co. PureFlow® is a registered trademark of Viega LLC.

All sales subject to Ridge Tool Company Terms and Conditions of Sales. Catalog Sheet No. R-22-E (822) Effective Date: August 16, 2022  
 ©2022 Ridge Tool Company. RIDGID and the Emerson logo are registered trademarks of Emerson Electric Co. or its subsidiaries in the US and other countries.  
 Any other trademarks belong to their respective holders.