



# HT1206UC2RC1

## HOME THEATER SURGE PROTECTION

Protect home theater equipment, home and office computers, and other electronics

Your home entertainment system, gaming gear and devices deserve 24/7 protection. Safeguard valuable electronics against voltage spikes and serious power events such as lightning-induced surges with advanced power protection. Loaded with features like fireproof and safe-fail technology, this surge protector guarantees your home and equipment stay safe. USB charging ports, network line protection, kink-resistant cord and a sleek design make it perfect for all your home entertainment needs.

### TYPICAL APPLICATIONS

- Home Theater Equipment
- Cable DSL/Modems
- Personal Computers
- Phone/Fax/Modem
- Cable and Satellite
- Consumer Electronics

### FEATURES

- Surge suppression: 2,880 J
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° off-set)
- Outlet type: 12 x NEMA 5-15R (surge-protected)
- USB charge ports: 4
- Transformer spaced outlets: 6
- Power cord: 6 ft.
- Dataline protection: Yes
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$500,000



## SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Plug Type	NEMA 5-15P
Input Voltage	125 VAC
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset
Switch	Yes

OUTPUT	
Outlet Type	12 NEMA 5-15R
Outlets - Total	12
Outlets - Widely Spaced	6
USB Charge Port	Yes
USB Charge Port Amperage	4.8 Amps (Shared)
USB Charge Port Quantity	4
USB Charge Port Type	Type A
USB Charge Port Voltage	5 VDC

HT1206UC2RC1

HOME THEATER SURGE PROTECTION

SPECIFICATIONS - CONT.

SURGE PROTECTION & FILTERING	
Attenuation	43 dB
Clamping Voltage	500V (H-N, H-G, N-G)
Coax Protection RG6	2 in 2 out Tin
EMI/RFI Filtration	Yes
Maximum Surge Current	90,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	60,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Network Protection RJ45	1 in / 1 out
Response Time	<1 Nanosecond
Surge Suppression (Joules)	2,880 J
PHYSICAL	
Color	Black
Form Factors Supported	Horizontal Mount in Variety of Other Applications
Keyhole Mounting Slots	Yes
Material of Construction	Plastic
Safety Covers	No

DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	13.41 x 3.66 x 32.72 cm
Physical Dimensions - Width/Height/Depth (mm)	134 x 37 x 327 mm
Physical Dimensions - Width/Height/Depth (in.)	5.28 x 1.44 x 12.88 in.
Weight (kg)	0.82 kg
Weight (lb)	1.80 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	21.01 x 40.23 x 4.19 cm
Shipping Dimensions - Width/Height/Depth (mm)	210.06 x 402.34 x 41.91 mm
Shipping Dimensions - Width/Height/Depth (in)	8.27 x 15.84 x 1.65 in.
Shipping Weight (kg)	0.94 kg
Shipping Weight (lbs.)	2.08 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL498A UL1449 3rd Edition cUL DoE FCC ICES-003
WARRANTY	
CEG Amount	\$500,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited