



CRC Industries NZ, Auckland NZ

I. Product Description

ADOS Nail It is a flexible, waterproof adhesive designed for bonding a wide range of substrates. It will cure to a tough rubbery bead with excellent permanent adhesion. Nail It eliminates nail pops, bridges minor framing gaps and reduces sound transmission. It is unaffected by moisture and can eliminate squeaks in tongue and groove flooring.

II. Features & Benefits

- No slump
- Excellent wet grab
- High bond strength
- Waterproof
- Tough & Flexible
- Convenient
- Stops nail pops

III. Application and Directions

PREPARATION:

- Surfaces to be bonded must be clean from any contamination and dry.
- Metals should be cleaned with a clean cloth soaked in ADOS Solvent N. Solvent should then be wiped from the surface with a clean, dry cloth.
- Use alcohol on glass, and for plastic consult the supplier for the recommended cleaning solvent.
- Do not use soap, detergent or water.
- When used in remedial work, all existing sealant must be removed with ADOS RTV Silicone Remover.

APPLICATION

1. Cut spout to desired bead size and puncture seal inside spout.
2. Apply with caulking gun forcing the adhesive onto surface.
3. Walls and Ceilings:
Apply 10 mm bead on all framing members. Apply 8 mm parallel beads near edge of framing timber where gypsum panels abut.
4. Position gypsum board in place and press firmly.
5. Use only flat boards, warped boards should not be used.
6. Follow nailing schedule as per manufacturers instructions.

CLEANING:

- Mineral Turpentine: For cleaning up excess adhesive and tools.

LIMITATION:

- Do not use on unlined expanded or extruded polystyrene foam.
- Not recommended for use on polystyrene, ABS plastic panels and prefinished vinyl covered gypsum panels.



CRC Industries NZ, Auckland NZ

IV. Typical Properties and Characteristics

Type	Solvent based adhesive
Composition	Synthetic elastomer, resins, fillers
Colour	Tan
Temperature Range	-30 °C to +80 °C
Reactivation	N/A
Viscosity	N/A
Coverage	10mm bead (approx 4m) 5mm bead (approx 8m)
Working Time	Up to 10 minutes

V. Package Description

Part Number	Size
8318	345 g

VI. Special Precautions**General:**

The solvents in ADOS Nail It are Highly Flammable. Keep away from naked flames, electrical appliances/lights, lighted cigarettes, etc. Use with adequate ventilation. Do not eat, drink or smoke while using. Store in a cool, well-ventilated area and indoor temperature must be between 5°C and 20°C. Dispose of empty containers safely. All unused product should be disposed of in conformance with local and HSNO regulations, do not contaminate water supply.

First Aid:

Swallowed – Give water to dilute. Do not induce vomiting. Get medical attention without delay.

Skin – Remove contaminated clothing and wash skin thoroughly with soap and water. Do not scrub skin.

Eyes – Hold open and flush with water for at least 15 minutes. Get medical attention without delay.

Inhalation – Remove to fresh air. If breathing with difficulty, get medical attention immediately.

Refer to Material Safety Data Sheet for more details.

TECHNICAL DATA SHEET Version 08/2012

PRODUCT WARRANTY: CRC offers a conditional warranty of this product for the period of 2 years from the date of manufacture.

DISCLAIMER: All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.