



Project Name: _____

Location: _____

Item #: _____ Qty: _____

Model: _____

UNDERCOUNTER HIGH-TEMP DISHWASHER with DIGITAL CONTROLS

MODEL: UC-18D-1 UC-18D-3



UC-18D-1 / UC-18D-3

RACK SIZES:

Dish Rack	20 in x 20 in	500mm x 500mm
Dish Max Height	12.8125 in	325mm
Plates Diameter	13.375 in	340mm

WATER CONSUMPTION

Per Rack 0.79 gal/cycle 3L/cycle

OPERATING CYCLES:

Cycle 1	120 sec
Cycle 2	180 sec
Cycle 3	240 sec
Cycle 4	300 sec

OPERATING CAPACITY

Racks per hour	30 / 20 / 15 / 12
Wash Tank Capacity	4.35 (gal) 16.46 (L)
Booster Capacity	2.16 (gal) 8 (L)

CYCLE TEMPERATURES

Wash	165°F	72°C
Rinse	180°F	82°C

WATER REQUIREMENTS

Inlet Temperature	140°F	60°C
Inlet Water Pressure	25-95psi	1.8 – 6.7kg/cm ²
Flow Pressure	15-25psi	1.0 – 1.8kg/cm ²

All specifications are dependent on water pressure and temperature

3RD PARTY APPROVALS



BLAKESLEE WARRANTY (USA / CANADA)

Blakeslee dishwashers are warranted for one year from date of installation against defective materials and workmanship.

Contact Blakeslee USA for details at service@blakesleeinc.com or 630.532.5021



This undercounter dishwasher is a state of the art electromechanical machine designed to deliver superior cleaning performance and productivity, using the least amount of energy, water and chemicals. This machine is the end result of tireless innovation and continuous improvement in this category, derived from the experiences and feedback from the global markets we serve.

FEATURES AND CONSTRUCTION

- 30 rack per hour / 2 minute cycle
- Built-in 6500 W booster
- 2940 W wash tank heater
- 180°F sanitizing rinse every cycle
- Built-in detergent and rinse aid dispensers with hook-up provided
- Removable wash and rinse arms (upper and lower)
- Triple filtering system with stainless steel filters to capture soil and debris
- Perfecta-Rinse™ : Extends the wash cycle time to ensure 180 degree final rinse
- Easy to read, simple to operate digital controls
- Digitalization of wash & rinse temperatures
- Double skin stainless steel door with security micro-switch
- Double skin stainless steel interior with deep formed rack supports
- Internal cavity and exterior panels – 304 stainless steel
- 316 stainless steel tank
- Noise – 59.3 dB(A)
- Built in drain pump provides versatility for installation locations
- 43W hMAX 31 ½” (10, 56 gal(US)/min**)
 - **Maximum Flow Rate
- Pump power – 0.75 HP/ 560W (89.8 gal (US) / min
 - *** Maximum Flow Rate



UNDERCOUNTER HIGH-TEMP DISHWASHER with DIGITAL CONTROLS



	WATER CONNECTION 3/4\"G
	DRAINING 15/16 inch
	ELECTRICAL SUPPLY

MODEL	DIMENSIONS	RACK SIZE	RACKS PER HOUR	ELECTRICAL	KW POWER	WEIGHT
UC-18D-1	34" x 30" x 44" (836 x 762 x 1118 mm)	20" X 20" (500 X 500mm)	30 / 20	220-240V/60Hz/1Ph	30.1A - 7.09kW	190 lbs (86.18 kg)
UC-18D-3	34" x 30" x 44" (836 x 762 x 1118 mm)	20" X 20" (500 X 500mm)	30 / 20	220-240V/60Hz/3Ph	20A - 7.09kW	190 lbs (86.18 kg)

All specifications are dependent on water pressure and temperature

*Other voltages available - contact factory