



Project: _____

Fixture Type: _____

Location: _____

Contact/Phone: _____

4" IC AND TC 1000 LUMEN INTERNALLY ADJUSTABLE LED DOWNLIGHT NEW CONSTRUCTION

IC4AL, TC4AL (10LM) RECESSED HOUSING



LENSED TRIMS

PRODUCT DESCRIPTION

Patent pending dedicated LED, Air-Loc® sealed new construction housing with integral internally adjustable light engine • Double wall, shallow housing construction • IC4AL series can be completely covered with insulation and installs in 2 x 6 construction • TC4AL series for use in non-insulated areas (If installed where insulation is present, the insulation must be pulled back 3" from all sides of the TC housing) • Fully sealed housing stops infiltration and exfiltration of air, reducing heating and cooling costs without the use of additional gaskets • LED housing is designed to provide 50,000 hours of life • 5 year limited warranty on LED components.

ENVIRONMENTALLY FRIENDLY, ENERGY EFFICIENT

- No harmful ultraviolet or infrared wavelengths
- No lead or mercury, RoHS compliant
- Comparable light output to 75W incandescent

PRODUCT SPECIFICATIONS

LED Light Engine LED array attached to cast aluminum sliding heatsink integrated directly with housing provides superior heat transfer to ensure long life of the LED • Replaceable light engine mounts directly to inner housing assembly and incorporates the latest generation, high lumen output LED array • LEDs are binned within a 3-step MacAdam Ellipse exceeding ENERGY STAR® requirements for superior fixture to fixture color uniformity • 2700K, 3000K, 3500K, or 4000K color temperatures available • 90 CRI minimum.

Optics Three field interchangeable, TIR optics available in 18°, 30° and 40° beam angles • Module can accommodate one 2-inch diameter beam control lens or filter • Adjustable light engine module provides up to 35° vertical adjustment and 360° rotation.

Aesthetic Trim Selections Adjustable perimeter frosted lensed trim • Shadow free, knife edge design blends seamlessly into ceiling • Trims are wet location approved for covered ceiling applications.

LED Driver Choice of dedicated 120 volt (120) driver or universal voltage (MVOLT) driver that accommodates input voltages from 120-277 volts AC at 50/60Hz • Power factor > 0.9 at 120V input • 120 volt only driver is dimmable with the use of most incandescent, magnetic low voltage and electronic low voltage wall box dimmers • Universal voltage driver is dimmable with the use of most 0-10V wall box dimmers • For a list of compatible dimmers, see [JUNOICLED-DIM](#).

Life Rated for 50,000 hours at 70% lumen maintenance.

Labels UL listed for U.S. and Canada for through-branch wiring, wet locations (covered ceilings) • Union made • UL and cUL.

Testing All reports are based on published industry procedures; field performance may differ from laboratory performance.

Specifications subject to change without notice.

HOUSING FEATURES

Housing IC4AL designed for use in IC (insulated ceiling) or non-IC construction • TC4AL designed for use in non-IC construction • Aluminum housing sealed for Air-Loc® compliance • Housing is vertically adjustable to accommodate up to a 1 1/2" ceiling thickness.

Junction Box Pre-wired junction box provided with (6) 1/2" and (1) 3/4" knockouts, (4) knockouts for 12/2 or 14/2 NM cable and ground wire • UL listed and cUL listed for through-branch wiring, maximum 4 #12 branch circuit conductors • Junction box provided with removable access plates • Knockouts equipped with pryout slots • Quick connect electrical connectors supplied as standard for fast, secure installation.



Mounting Frame 22-gauge die-formed galvanized steel mounting frame • Rough-in section (junction box, mounting frame, housing and bar hangers) fully assembled for ease of installation.

Real Nail 3 Bar Hangers Patented (US Patent D552,969)

Real Nail® 3 bar hangers: telescoping system permits quick placement of housing anywhere within 24" O.C. joists or suspended ceilings • Includes removable nail for repositioning of fixture in wood joist construction • Integral T-bar notch and clip for suspended ceilings.



DIMENSIONS



4 1/2" CEILING CUTOUT

ELECTRICAL DATA

Dedicated 120V Only Driver Option (120) 120V

Input Power	16.4W (+/-5%)
Input Current	0.15A
Frequency	50/60Hz
EMI/RFI	FCC Title 47 CFR, Part 15, Class B (Residential)
Minimum starting temp	-25°C (-13°F)

Universal Voltage Driver (MVOLT ZT)

120V	277V
Input Power	16.0W (+/-5%)
Input Current	0.06A
Frequency	50/60Hz
EMI/RFI	FCC Title 47 CFR, Part 15, Class A (Commercial)
Minimum starting temp	-20°C (-4°F)

Lutron Hi-Lume® LED Driver (MVOLT ECOD)

120V	277V
Input Power	16.4W (+/-5%)
Input Current	0.15A
Frequency	50/60Hz
EMI/RFI	FCC Title 47 CFR, Part 15, Class A (Commercial)
Minimum starting temp	0°C (32°F)

4" IC AND TC 1000 LUMEN INTERNALLY ADJUSTABLE LED DOWNLIGHT NEW CONSTRUCTION

IC4AL, TC4AL (10LM) RECESSED HOUSING
LENSED TRIMS

ORDERING INFORMATION Housing and trim can be ordered together or separate, but will always ship separately.

Example: IC4AL 10LM 27K 90CRI FL 120 FRPC

Series	Lumens	Color Temperature	CRI	Distribution	Voltage	Driver	Territory
IC4AL 4" LED Internally Adjustable New Const. IC Downlight	10LM 1000 Nominal Lumens	27K 2700K 30K 3000K 35K 3500K 40K 4000K	90CRI 90+ CRI	FL Flood NFL Narrow Flood SP Spot	120 120V MVOLT Multi-Volt (120-277V)	FRPC Forward / Reverse Phase Cut ZT 0 - 10V Dimming Driver	CP Chicago Plenum

Notes: 120 must be ordered with FRPC. MVOLT must be ordered with ZT

Example: TC4AL 10LM 27K 90CRI FL MVOLT ECOD

Series	Lumens	Color Temperature	CRI	Distribution	Voltage	Driver	Territory
TC4AL 4" LED Internally Adjustable New Const. Non IC Downlight	10LM 1000 Nominal Lumens	27K 2700K 30K 3000K 35K 3500K 40K 4000K	90CRI 90+ CRI	FL Flood NFL Narrow Flood SP Spot	MVOLT Multi-Volt	ECOD Lutron Hi-Lume EcoSystem, 1% Dimming	CP Chicago Plenum

TC4AL is not ENERGY STAR® or T24 compliant

Trim/Description



- 41L BRZ** 4" Adjustable Lens Shower Trim - Bronze
41L SC 4" Adjustable Lens Shower Trim - Satin Chrome
41L WH 4" Adjustable Lens Shower Trim - White



Trim Size: 5" O.D.

Note: In Canada when insulation is present, Type IC fixtures must be used.

Accessories (ordered separately)

Catalog Number	Description
CGF 200 MPINK	Color Glass Filter - 2" Diameter - Medium Pink
CGF 200 WRED	Color Glass Filter - 2" Diameter - Warm Red
CGF 200 DLTBLUE	Color Glass Filter - 2" Diameter - Daylight Blue
CGF 200 MBLU	Color Glass Filter - 2" Diameter - Medium Blue
CGF 200 MAMB	Color Glass Filter - 2" Diameter - Medium Amber
CGF 200 MGRN	Color Glass Filter - 2" Diameter - Medium Green
DGF 200 DRED	Dichroic Glass Filter - 2" Diameter Red
DGF 200 MGRN	Dichroic Glass Filter - 2" Diameter Medium Green
DGF 200 MBLU	Dichroic Glass Filter - 2" Diameter Medium Blue
DGF 200 DYEL	Dichroic Glass Filter - 2" Diameter Yellow (Dichroic)
DGF 200 MAGEN	Dichroic Glass Filter - 2" Diameter Magenta
DGF 200 CYAN	Dichroic Glass Filter - 2" Diameter Cyan
DCCF 200 HL4250	Dichroic Color Correction Filter - 2" Diameter - Halogen - to - Daylight
DIFF 200	Diffusion Glass Lens - 2" Diameter
UVF 200	UV Filter Lens - 2" Diameter
HCLBL 200	Hexagonal Cell Louver - Black - 2" Diameter
LSPREAD 200	Linear Spread Glass Lens - 2" Diameter
PRISM 200	Prismatic Glass Lens - 2" Diameter
TIR2 SPT	TIR Optic - Spot
TIR2 NFLD	TIR Optic - Narrow Flood
TIR2 FLD	TIR Optic - Flood

4" IC AND TC 1000 LUMEN INTERNALLY ADJUSTABLE LED DOWNLIGHT NEW CONSTRUCTION


IC4AL, TC4AL (10LM) RECESSED HOUSING

LENSED TRIMS

PHOTOMETRICS

PHOTOMETRIC REPORT

Test Report: PT09153003R
Catalog No: IC4AL 10LM 35K 90CRI
SP 120 FRPC with 41L WH and
Spot Optic
Watts: 16.4
Lumens: 848
Luminaire LPW: 52




Candlepower Distribution (Candelas)

Degrees Vertical	Candela
0°	142
5°	191
10°	271
15°	452
20°	828
25°	1735
30°	3387
35°	4633
40°	3756
45°	2039
50°	903
55°	318
60°	150
65°	84
70°	54
75°	32
80°	15
85°	4
90°	0

PHOTOMETRIC REPORT

Test Report: PT09152923R
Catalog No: IC4AL 10LM 35K 90CRI
NFL 120 FRPC with 41L WH and
Narrow Flood Optic
Watts: 16.4
Lumens: 867
Luminaire LPW: 53




Candlepower Distribution (Candelas)

Degrees Vertical	Candela
0°	135
5°	183
10°	233
15°	468
20°	1208
25°	2208
30°	2836
35°	3030
40°	2782
45°	2169
50°	1288
55°	408
60°	149
65°	93
70°	53
75°	27
80°	12
85°	3
90°	0

PHOTOMETRIC REPORT

Test Report: PT090152903R
Catalog No: IC4AL 10LM 35K 90CRI
FL 120 FRPC with 41L WH and
Flood Optic
Watts: 16.4
Lumens: 936
Luminaire LPW: 57







Candlepower Distribution (Candelas)

Degrees Vertical	Candela
0°	139
5°	254
10°	487
15°	826
20°	1280
25°	1782
30°	2142
35°	2305
40°	2226
45°	1716
50°	1107
55°	619
60°	405
65°	224
70°	95
75°	28
80°	10
85°	1
90°	0

CBCP • Centerbeam candlepower
FC • Footcandles at beam center (aim point)

In vertical aiming applications, aim point (X) is determined by dividing distance from the wall (D) by the tangent of the desired aim angle (A) (0.5774 for 30°, 1.0 for 45°).



FIXTURE	Beam Type	Beam Spread°	CBCP	0°				30°			30°				
				MH	FC	L	W	FC	L	W	D	FC	X	L	W
IC4AL (10LM) LED, 3500K Spot	SP	18° 	4633	4	290	1.3	1.3	188	1.7	1.5	2	145	3.5	2.7	1.3
				6	129	1.9	1.9	84	2.6	2.2	3	64	5.2	4.1	1.9
				8	72	2.5	2.5	47	3.4	2.9	4	36	6.9	5.5	2.5
				10	46	3.2	3.2	30	4.3	3.7	5	23	8.7	6.9	3.2
				12	32	3.8	3.8	21	5.1	4.4	6	16	10.4	8.2	3.8
IC4AL (10LM) LED, 3500K Narrow Flood	NFL	30° 	3030	4	189	2.1	2.1	123	2.9	2.5	2	95	3.5	5.5	2.1
				6	84	3.2	3.2	55	4.4	3.7	3	42	5.2	8.2	3.2
				8	47	4.3	4.3	31	5.9	5.0	4	24	6.9	10.9	4.3
				10	30	5.4	5.4	20	7.3	6.2	5	15	8.7	13.7	5.4
				12	21	6.4	6.4	14	8.8	7.4	6	11	10.4	16.4	6.4
IC4AL (10LM) LED, 3500K Flood	FL	40° 	2305	4	144	2.9	2.9	94	4.1	3.4	2	72	3.5	9.7	2.9
				6	64	4.4	4.4	42	6.1	5.0	3	32	5.2	14.5	4.4
				8	36	5.8	5.8	23	8.1	6.7	4	18	6.9	19.3	5.8
				10	23	7.3	7.3	15	10.2	8.4	5	12	8.7	24.2	7.3
				12	16	8.7	8.7	10	12.2	10.1	6	8	10.4	29.0	8.7

Multipliers: 27K - 0.93
30K - 0.96
35K - 1.00
40K - 1.03