



**MATERIAL**

PLASTIC HOUSING : ABS high-impact UL94V-0 thermoplastic  
INSERT: Brass 3604 Surface gold plating

**PHYSICAL CHARACTERISTICS**

OPERATING TEMPERATURE RANGE : -10 C TO 60 C  
STORAGE TEMPERATURE RANGE : -40 C TO 68 C  
HUMIDITY : 10%~90%RH

**ELECTRICAL**

IMPEDANCE: 75 ohm  
FREQUENCY RANGE: 0~3 GHz  
WORKING VOLTAGE: 250 VRMS max.  
DIELECTRIC WITHSTANDING VOLTAGE: 500VRMS min.  
VSWR: 1.35 max  
CONTACT RESISTANCE: 1.Center Contact: 5 Milliohms Max.  
2.Outer Contact: 1 Milliohms Max.  
INSULATOR RESISTANCE: 1000 Megohms min.

Colors Available: White

Scale		1.5:1			All Copy Rights Reserved			
3rd Angle Projection					RCA SNAP IN MODULE, GOLD-PLATED-Black Bezel			
Unit		mm			SCP P/N <b>243BK-XX</b>			
Date		2015-09-16						
Tolerance					Drawn by		Checked by	
~20	~50	~150	150~	ANGLE				
±0.2	±0.4	±0.5	±1.5	±2°	FHL		Santiago	