



Non-Volatile Matter	95.00 - 97.50%
UL Certified	Yes

Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

Directions for Use

RECOMMENDED FOR: Wood; Ceramic Tile; Terrazzo; Marble; Magnesite; Concrete; Glazed Tile; Synthetic Sports Floors; Sealed or Painted Surfaces; Formica Walls or Counters; Aluminum or Stainless Steel; Furniture and Fixtures; Lockers and File Cabinets; Sealed Masonry Surfaces. DIRECTIONS: DUST MOP AND CLOTH TREATMENT: Sprinkle or apply coarse spray treatment directly on mops or cloths. Before using mops hang overnight with wicks down. On new or freshly laundered mops – apply 2 ounces per linear foot of dust mop. Daily care: Shake out dust and spread wicks apart, then retreat with 1 ounce per linear foot. Hang treated mop in well-ventilated area until next day's use. Do not overtreat mop. Heavily soiled cloths or dust mops should be laundered and retreated.

Certifications

Classified by Underwriters Laboratories, Inc. as to slip resistance. (186S).

A high-quality dust mop treatment formulated to clean and protect seals and finishes. Daily dust mopping with Super Hil-Tone increases the life and beauty of your floors by reducing the abrasive effects of tracked in dirt. Treatment with Super Hil-Tone provides excellent resistance to black heel marks, scuffing, and scratching.

Features & Benefits

- Formulated to clean and protect seals and finishes
- Increases the life and beauty of floors to keep them looking great
- Reduces the abrasive affects of tracked in dirt

Item Number & Unit of Measure

Item Number	HIL0021507
Unit of Measure	5 gal Pail

Specifications

Color	Light Yellow
Appearance	Clear to Slightly
Fragrance	Oil
Formula Type	Liquid
Dilution Ratio	RTU
PH	N/A