



Solids Content	20
Coverage SqFt/Gallon	1500-2000
Dry Time (hrs.)	1
Sheen	Satin
UL Certified	Yes

Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

Directions for Use

Preparation: Strip other finishes from the floor with Hillyard Devastator[®] or Power-Strip following label directions. Use floor machine with black pad or brush (do not use abrasive pads on tile containing asbestos). Remove stripping solution with a wet vacuum. Heavy rinse with Hillyard Nutra-Rinse[®] mixed 4 oz per gallon of water and pick up with the wet vacuum. Damp mop all flooring twice with clean, cool water. Allow the floor to dry. **Application:** Before opening container, gently and slowly rock it back and forth for 10 seconds to mix flattening agent. Do not use a sealer. Apply 3 to 5 coats of Satin Floor Finish with a clean synthetic flat mop. Allow each coat to dry a minimum of 30 minutes before applying the next. For best results do not use over existing floor finish or sealer as this will affect gloss, and do not coat over Satin Floor Finish with another finish. Apply with a flat mop applicator only. **NOTE:** Allow for longer dry time between coats of finish if the humidity is above 80% or the floor temperature is below 60 °F (16°C). **Maintenance:** Use a Hillyard Super Hil-Tone[®] treated dust mop daily to remove loose dirt and grit. Damp mop or autoscrub finish as scheduled with Hillyard Assurance[®], Super Shine-All[®], or Top Clean[®]. Do not buff. **Floor Pad Recommendations: Stripping:** black; **Scrub and Recoat:** blue; **Autoscrubbing:** red. **NOTICE:** Do not use an ammoniated cleaner for daily care. Do not pour unused finish or seal back into the original container.

A special low gloss floor coating. It lowers the cost of clean by lowering the frequency of cleaning. It provides excellent resistance to black marks, scuffs, scratches, and heel marks. No buffing is required or desired. Recommended for assisted living and nursing homes, especially those that are dedicated to the care of Alzheimer's patients. Also recommended for other situations where a low gloss surface or minimal reflection is desired. Geriatric experts have concluded that shiny surfaces may appear wet to an Alzheimer's patient.

Features & Benefits

Special low gloss floor coating

Recommended for assisted living and nursing homes

No buffing is required or desired

Item Number & Unit of Measure

Item Number	HIL0054106
Unit of Measure	1 gal Bottle

Specifications

Color	White
Appearance	Milky Emulsion
Fragrance	Non-Objectionable
Formula Type	Liquid
Dilution Ratio	RTU
PH	8.00 - 9.00
Non-Volatile Matter	19.50 - 20.50%

