

HPH J-Hooks & Bridle Rings with Rare-Earth Magnets



TOP MOUNT




SIDE MOUNT

Today, organizing and managing low voltage cables being used in non-permanent applications is easy, safe and quick to install. What is the secret? These **Rare Earth Magnets** integrated with both the **HPH J-Hooks** and **Bridle Rings**. A great solution for those low voltage temporary installations.

Features and Benefits

- Fast Installation Saves Time and Money
- Removable and Reusable
- Easy to Install, No Drilling Required
- Simple to Re-route
- Available in Top Mount (V), and Side Mount (H)
- Support Category Cables: Cat5e/6/6a/7 and Coaxial Cables: CCTV, CATV



Product Specifications

Rare Earth Magnets

- Nominal Breakaway Strength: 90 lbs (Top Mount Only)
Magnet breakaway strength is very dependent on the surface to which magnet is attached. Always pull test for strength.



BRIDLE RINGS

HPH J-Hooks & Bridle Rings with Rare-Earth Magnets

HPH J-HOOKS

Top Mount



Side Mount



BRIDLE RINGS

Ordering Information:



HPH J-Hooks with Magnets

Size	CABLE CAPACITY			Color	SIDE MOUNT	TOP MOUNT	Qty
	Cat5e	Cat6	Cat6A		Part No.	Part No.	
1" Size 16	20	20	10	White	HPH16MH-10	HPH16MV-10	10 / Box
				Blue	HPH16MH-10BL	HPH16MV-10BL	
				Black	HPH16MH-10BK	HPH16MV-10BK	
				Red	HPH16MH-10R	HPH16MV-10R	
2" Size 32	90	60	35	White	HPH32MH-10	HPH32MV-10	10 / Box
				Blue	HPH32MH-10BL	HPH32MV-10BL	
				Black	HPH32MH-10BK	HPH32MV-10BK	
				Red	HPH32MH-10R	HPH32MV-10R	

Magnet breakaway strength is very dependent on the surface to which magnet is attached. Always pull test for strength.


Bridle Rings with Magnets

	Part No.	Qty
Bridle Ring, 1-1/4", with top mount magnet	JH807M-10	10 / Box
Bridle Ring, 2", with top mount magnet	JH808M-10	10 / Box



Magnets

	Part No.	Qty
Rare Earth Magnet in housing with 1/4" - 20 female threads	MAG420-10	10 / Box



WARNINGS READ BEFORE USE:

Rare earth magnets are extremely strong and potentially dangerous. View warnings at platinumtools.com/sections/magnet_warnings or scan the code.

