



CSP600WSU | PROFESSIONAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower Professional Series CSP600WSU Surge Protector is ideal for Home/Office protection with 1,200 joules, 6 swivel outlets, 2 USB charge ports (2.4 Amp shared), and a convenient wall-tap design. The surge protector is ideal for protecting personal computers, phones/fax/modems, printers, stereos, and other electronics. Its two USB ports are perfect for keeping tablets, smart phones, and other rechargeable electronics ready to use.

The CSP600WSU features six outlets, wall-tap plug, MOV technology to guard the surge protector and connected electronics against line abnormalities and lightning surges, while EMI/RFI filters block unwanted line noise. This surge protector comes with a 1-Year Limited Warranty and a \$75,000 Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 1,200 J
- Volts: 125 V
- Plug type: NEMA 5-15P
- Outlet type: 6 NEMA 5-15R (surge-protected)
- USB charge ports: 2
- EMI/RFI Filtration: Yes
- LED indicators: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$75,000

SPECIFICATIONS

INPUT	
Circuit Breaker	None
Cord Length	Wall-tap
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Wall-tap
OUTPUT	
Outlet Type	6 NEMA 5-15R
Outlets - Total	6
USB Charge Port	Yes
USB Charge Port Amperage	2.4 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Standard	Type A
USB Charge Port Type	2 Type A
USB Charge Port Voltage	5 VDC

SURGE PROTECTION & FILTERING - CONT	
Attenuation	32 dB
Clamping Voltage	500V (H-N, H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	60,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	30,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	1,200 J

CSP600WSU

PROFESSIONAL SURGE PROTECTOR

SPECIFICATIONS - CONT.

PHYSICAL	
Color	Black
Form Factors Supported	Direct plug
Material of Construction	Plastic
DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	10.67 x 16.26 x 6.35 cm
Physical Dimensions - Width/Height/Depth (mm)	107 x 163 x 64 mm
Physical Dimensions - Width/Height/Depth (in.)	4.2 x 6.4 x 2.5 in.
Weight (kg)	0.40 kg
Weight (lb)	0.88 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	19.2 x 6.22 x 10.72 cm
Shipping Dimensions - Width/Height/Depth (mm)	192.02 x 62.23 x 107.19 mm
Shipping Dimensions - Width/Height/Depth (in)	7.56 x 2.45 x 4.22 in.
Shipping Weight (kg)	0.45 kg
Shipping Weight (lbs.)	1.00 lbs.

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1363 UL498A
WARRANTY	
CEG Amount Value	\$75,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited