













## **Specifications**















Resolution Intelligent Video

4.0mm Fixed Lens

## Summary

This MEGApix® IVA™ IP camera is your gateway to powerful video analytics features. It is NDAA compliant and provides 2.1MP/1080p resolution at real-time 30fps. The MEGApix IVA cameras have a powerful engine to detect and classify people and vehicles in real-time. IVA+ license upgrade offers advanced Video Content Analysis detection capabilities. This camera includes a 4.0mm fixed lens, simultaneous H.265/H.264/MJPEG codec support and Star-Light Plus™ color in neartotal darkness technology for quality video in any lighting condition, all in an IP67 dust-tight and waterproof bullet housing. All MEGApix® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

## **Features**

- 2.1MP/1080p 1/2.8" image sensor at real-time 30fps
- Star-Light Plus<sup>™</sup> color in near-total darkness technology
- Intelligent Video Analytics (IVA)
- Extended Intelligent Video Analytics (IVA+ license required)
- Seamless integration and control of IVA rules with DW Spectrum® IPVMS
- · Reduce false alarms
- · Increase your recording storage with logic rules and smart recording
- · 4.0mm fixed lens
- True Wide Dynamic Range (WDR)
- Triple codecs (H.265, H.264, MJPEG) with simultaneous streaming
- 100' Smart IR™ with intelligent camera sync
- Smart DNR<sup>™</sup> 3D digital noise reduction
- True day/night mechanical IR cut filter
- Programmable privacy zones
- · Auto gain control (AGC)
- Auto white balance (AWB)
- · Motion detection
- Micro SD/SDHC/SDXC class 10 card slot (card not included)
- PoE class 2 and DC12V
- UL listed
- NDAA compliant
- IP67 dust-tight and waterproof to 3 feet
- 5 year warranty



•	Haien
IMAGE	
Image sensor	2.1MP/1080p 1/2.8" CMOS
Total pixels	1945 (H) X 1109 (V)
Minimum scene illumination	0.09 lux (color)
	0.0 lux (B/W)
LENS	T
Focal length	4.0mm, F2.6
Lens type	Fixed lens
HFOV / VFOV IR distance	86° / 46°
OPERATIONAL OPERATIONAL	100ft range
OFERATIONAL	IVA license: intrusion, line crossing, counting line,
	loitering, enter, exit, tamper
Intelligent Video Analytics	IVA+ license: object removed, tailgating, direction,
	stopped, appear, disappear, object left
Shutter mode	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/15 ~ 1/32000
Slow shutter	1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10
Auto gain control	Auto
Day and night	Auto, day (color), night (B/W)
Smart DNR™ 3D digital noise reduction	3D-DNR
Wide Dynamic Range (WDR)	True WDR
Wide Dynamic Range (WDR) dB	120dB
Privacy zone	16 programmable privacy masks
Mirror and flip	Yes
Alarm notifications	Notifications via e-mail notifications,
	FTP and SD card recording
Memory slot	Micro SD / SDHC / SDXC (card not included)
NETWORK LAN	D 145 (10 /100Dana T)
Video compression type	RJ45 (10/100Base-T) H.265, H.264, MJPEG
video compression type	
Resolution	H.265: 2.1MP/1080p, 720p, VGA, D1, CIF H.264: 2.1MP/1080p, 720p, VGA, D1, CIF MJPEG: 1280x720, 800x600, VGA, 768x432, D1, CIF
Resolution	MJPEG: 1280x720, 800x600, VGA, 768x432, D1, CIF
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps ~ 10Mbps, multi-rate for preview and recording
Bitrate control	Multi-streaming CBR/VBR at H.264, H.265 (controllable
	frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4, IPv6
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP,
1100001	ICMP, SNMPv1/v2/v3 (MIB-2), ONVIF
Security	HTTPS (TLS), IP filtering, 802.1x, digest authentication
	(ID/PW)
ONVIF conformance	Yes
	OS: Windows*, Mac* OS, Linux*
Web viewer	Browser: Internet Explorer®, Google Chrome®, Mozilla Firefox®, Safari®
1102 1101101	NOTE: Chrome browser is recommended for IVA
	configuration
Video management software	DW Spectrum* IPVMS
ENVIRONMENTAL	
Operating temperature	-4°F ~ 122°F (-20°C ~ 50°C)
Operating humidity	10-90% (non-condensing)
IP rating	IP67-rated
Other certifications ELECTRICAL	UL listed, CE, FCC, RoHS
ELECTRICAL	DC 101/ DaE (IEEE 000 7-6 Class 2)
Power requirement	DC 12V, PoE (IEEE 802.3af Class 2). (Adapter not included)
	DC12V: max 4.5W
Power consumption	PoE: max 6.0W
MECHANICAL	
Material	Aluminum bullet housing
Dimensions	6.41" x 2.65" (163 x 67.5 mm)
Weight	1.1 lbs (0.5kg)
Warranty	5 year warranty

(: 866.446.3595



: sales@digital-watchdog.com





